

STAINLESS STEEL CORNER GUARDS

PART 1 - GENERAL

1.01 DESCRIPTION

- A. This Section describes the requirements for furnishing and installing prefabricated-type stainless steel corner guards at Basement and First Floor locations as required.

1.02 PRODUCT DELIVERY, STORAGE, AND HANDLING

- A. Deliver materials in manufacturer's original, unopened containers.
- B. Deliver stainless steel corner guards with protective covering.

1.03 PROTECTION

- A. Protect adjacent existing and newly placed construction and finishes against damage.
- B. Protect this work against damage during installation, and maintain protection as necessary until completion of other construction operations.

PART 2 - PRODUCTS

2.01 CORNER GUARDS

- A. Approved Manufacturers: American Floor Products Co. Inc. "Lunar", Pawling Corporation "CG50", Tubular Specialties, Inc. "CP-3548 x 16", Wilkinson Company, Inc. "WCG-3/4"C" or approved equal.
- B. Material: 16-gauge stainless steel with satin finish.
- C. Lengths: 48-inches.
- D. Adhesive: Epoxy.

PART 3 - EXECUTION

3.01 INSPECTION

- A. Do not install exposed covers and accessories until painting is complete at same location.

3.02 INSTALLATION

- A. Install corner guards in accordance with manufacturer's instructions.
- B. Clean corner of walls to receive corner guards to remove loose particles and dust. Apply cement to back of corner guard and press into place. Remove excess cement from around edges and allow to set before removing protective covering.

3.03 COMPLETION

- A. When complete, each assembly shall be set square, plumb and level and securely anchored.

- B. Exposed surfaces shall be clean and free from scratches, dents, tool marks, stains, discoloration, and other defects and damage.

END OF SECTION