



- GENERAL NOTES**
- A. REFER TO CIVIL FOR TOP OF PAVING/FINISHED WALL ELEVATIONS AND SURFACE DRAINAGE INFORMATION OUTSIDE OF BUILDING ENVELOPE.
 - B. REFER TO LANDSCAPE FOR PAVING PATTERNS RELATED DIMENSIONS.
 - C. REFER TO CIVIL FOR FINISHED TOP OF WALL AND TOP OF CURB ELEVATIONS.
 - D. TOP OF SLAB ELEVATIONS REFER TO TOP OF STRUCTURAL SLAB - SEE STRUCTURAL DRAWINGS.
 - E. TOP OF CONC ELEVATIONS REFER TO TOP OF CAST-IN PLACE CONCRETE ABOVE STRUCTURAL SLAB.

- KEY NOTES**
- 1. LOCATION OF TRENCH DRAIN. SEE MECHANICAL FOR LOCATION OF DRAIN DISCHARGE THROUGH SLAB AND RELATED PLUMBING.
 - 2. LOCATION OF TRENCH DRAIN IN SURFACE PAVEMENT - SEE CIVIL.
 - 3. EXTENT OF SLAB ON GRADE - REFER TO CIVIL FOR CURB LOCATIONS AND TOP OF PAVEMENT ELEVATIONS.
 - 4. OUTLINE OF VENDOR DESIGNED FOUNTAIN - MATERIALS/FORM TO BE DETERMINED.
 - 5. OUTLINE OF SITE FEATURES ABOVE STRUCTURAL SLAB - SEE CIVIL AND LANDSCAPE DRAWINGS.
 - 6. TAPER 4" LEADING EDGE OF CAST-IN PLACE CONCRETE CURB 1/4" TO DRAIN. SEE WALL SECTIONS AND ASSOCIATED DETAILS FOR CONCRETE PROFILE ABOVE ELEVATION 334'-3".
 - 7. COLUMN BASE - SEE STRUCTURAL FOR PROFILE OF CONTINUOUS CONCRETE CURB BETWEEN COLUMN BASES - ALIGN WITH COLUMN BASE TOP OF CONCRETE ELEVATIONS.
 - 8. OPENING FOR MECHANICAL - SEE STRUCTURAL. LOCATE BOTTOM OF 10" HIGH OPENING AT 12'-0" AFF.
 - 9. OUTLINE OF RECESSED LIGHT FIXTURES LOCATED IN CURB ABOVE.

LEGEND

AREA OF SECONDARY SLAB