



MATERIAL LEGEND

Division 03 Concrete

03 00 00.A CAST-IN-PLACE CONCRETE
B #4 BARS @ 12" O.C. EACH WAY
03 45 00.A ARCHITECTURAL PRECAST CONCRETE

Division 04 Masonry

04 05 19.4 MASONRY ANCHORAGE & REINFORCING;
L 5x5x3/8 LEDGER ANGLE W/ 1" BEARING
EACH SIDE, TYP.

04 21 13.A BRICK MASONRY
B 8' SOLDIER COURSE
04 22 00.A CONCRETE UNIT MASONRY

Division 05 Metals

05 12 13.A ARCHITECTUALLY EXPOSED STRUCTURAL STEEL,
W/ 4x16 STEEL HEADER

05 31 00.A METAL CEILING

05 41 00.A STRUCTURAL METAL STUD FRAMING:
600S162-54 @ 16' O.C. W/ 1/2" PLYWOOD
W/ 6 SCREWS @ 6' O.C.

B 400S162-43 @ 16' O.C.

C 400S162-54 BRACE @ 16' O.C. W/ (3) *8
SELF-DRILLING SCREWS @ EACH END

D 600S162-54 BRACE @ 16' O.C.

E EXTEND 600S162-54 @ 16' O.C. W/ 1/2"
PLYWOOD W/ 6 SCREWS @ 6' O.C.

F 600S162-54 @ 16' O.C.

Division of Thermal & Moisture Protection

Ø1 42 43.A COMPOSITE ALUMINUM WALL PANELS

Division 08 Openings

08 44 12.A ALUMINUM CURTAIN WALLS
B SUNSCREEN MOUNTED TO VERTICAL MULLIONS

KEY NOTES

- (01) ADDITIONAL FRAMING AS REQ'D FOR SUPPORT
 (02) SEE A/6.25 FOR ADDITIONAL LOUVER DETAILS
 (03) STEEL BEYOND SHOWN DASHED

MASONRY JOINT LEGEND

C.J. - CONTROL JOINT - TYPICAL MASONRY JOINT UNLESS NOTED OTHERWISE // BACKER ROD & SEALANT TYPICAL. NO MORTAR OR BRIDGING OF JOINT WITH REINFORCING OR LINTEL ANGLES

D.J. - DRIFT/ISOLATION JOINT - 1 1/8" WIDTH // BACKER ROD - 1" DIA. NO MORTAR OR BRIDGING OF JOINT WITH REINFORCING OR LINTEL ANGLES. SEE ASSOCIATED DETAILS FOR FLASHING & SEALANT TREATMENT OF SPECIFIC JOINTS.

B.B. - BOND BREAKER - 20 GAUGE STAINLESS STEEL OR MATERIAL CALLED OUT IN ASSOCIATED DETAILS FULL WIDTH OF BRICK LENSES 1/8" - ALIGN W/ BACK FACE OF BRICK. 1/2" GAP BETWEEN BRICK AND PRECAST OR CONCRETE

MATERIAL LEGEND

- | | |
|---|---|
|  | Clear Thermal Glazing with Solar Coating. |
|  | Thermal Glazing with Ceramic Frit. |
|  | Thermal Glazing with Ceramic Frit and Spandrel Paint. |
|  | Brick A. |
|  | Brick B. |
|  | Metal Panel. |
|  | Painted Concrete. |

