



- MATERIAL LEGEND**
- Division 06 Wood & Plastics**
06 16 00A GLASS-MAT GYPSUM SHEATHING
- Division 04 Masonry**
04 05 13A MASONRY ANCHORAGE AND REINFORCING
04 21 13A BRICK MASONRY
- Division 05 Metals**
05 41 00A STRUCTURAL METAL STUD FRAMING
- Division 01 Thermal & Moisture Protection**
01 21 00D WALL CAVITY INSULATION
01 25 10A BREATHABLE MEMBRANE
B BREATHABLE MEMBRANE TAPE
C LIQUID APPLIED BREATHABLE MEMBRANE
01 60 00A SILICONE SHEET
01 62 00A SHEET METAL FLASHING AND TRIM
B METAL CLAD WEATHER BARRIER
C FLASHING MEMBRANE
01 92 00A EXTERIOR SEALANT
- GENERAL NOTES**
FILL VOIDS AND TRANSITIONS IN SHEATHING WITH BACKER MATERIAL TO PROVIDE SUPPORT OF FLASHING MEMBRANE

- GENERAL BARRIER NOTES:**
1. TEST ALL MATERIALS, ADHESIVES, PRIMERS, ETC. FOR ADHESION AND COMPATIBILITY PRIOR TO BEGINNING INSTALLATION.
2. FOLLOW MANUFACTURER'S INSTALLATION RECOMMENDATIONS.
3. PRIME ALL SURFACES AS RECOMMENDED BY THE MANUFACTURER.
4. CLEAN AND PREPARE SUB-STRATES AS RECOMMENDED BY THE MANUFACTURER.
5. FOLLOW MANUFACTURER'S RECOMMENDATIONS FOR APPLYING MATERIALS OVER CONCRETE INCLUDING PRIMING, CLEANING AND CONCRETE MOISTURE CONTENT.
6. INSTALL BREATHABLE MEMBRANE USING FASTENERS, TAPE AND PROPER OVERLAP AND TRIMMING AS INSTRUCTED BY THE MANUFACTURER.
7. COVER HOLES IN BREATHABLE MEMBRANE BUILDING WRAP WITH COMPATIBLE TAPE AS RECOMMENDED BY THE MANUFACTURER.
8. SEE EXTERIOR WALL DETAIL SHEETS FOR CONDITIONS NOT SHOWN HERE.