



- MATERIAL LEGEND**
- Division 03 Concrete**
- 03 30 00.A CAST IN PLACE CONCRETE CURB
 - 03 45 00.A ARCHITECTURAL PRECAST CONCRETE
- Division 04 Masonry**
- 04 21 13.A BRICK MASONRY
 - B MASONRY ANCHOR
- Division 05 Metals**
- 05 12 00.A STRUCTURAL STEEL
 - B VERTICAL 'C' SECTION
 - C L 3x3 1/2 x 23 1/2 GALVANIZED ANGLE
 - 05 31 00.A METAL DECKING
 - B BENT STEEL DECK ATTACHMENT ANGLE
 - 05 41 00.A STRUCTURAL METAL FRAMING
 - B 3x3x1/8 GAUGE CONT. ANGLE EACH SIDE
 - C METAL FACED SHEATHING
- Division 06 Wood, Plastics & Composites**
- 06 16 00.A SHEATHING
- Division 07 Thermal & Moisture Protection**
- 07 21 00.A INS-1 BATT INSULATION
 - B INS-2 UNFACED GLASS SEMI-RIGID INSULATION
 - C INS-3 EXTRUDED POLYSTYRENE INSULATION
 - D INS-4 WALL CAVITY INSULATION
 - E INS-5 CURTAIN WALL INSULATION
 - F INS-6 SPRAY APPLIED INSULATION
 - G VAPOR RETARDER
 - 07 25 10.A BREATHABLE MEMBRANE
 - B BREATHABLE MEMBRANE TAPE
 - 07 41 13.A METAL ROOF PANEL
 - C PANEL CLIP
 - D SELF ADHERED HIGH TEMPERATURE SHEET AND SLIP SHEET
 - E 4" DEEP 1/2" FURRING AT 24" O.C. HORIZONTAL
 - 07 42 43.A COMPOSITE WALL PANEL
 - B FORMED ALUMINUM COPING
 - C EXTEND FORMED ALUMINUM COPING TO BRICK FACE BEYOND
 - D OUTLINE OF FORMED ALUMINUM COPING CAP ABOVE
 - 07 53 23.A EPDM MEMBRANE ROOFING SYSTEM W/ BALLAST
 - B SUBSTRATE BOARD
 - C 4" POLYISOCYANURATE INSULATION
 - D 2 1/2" MINIMUM TAPERED POLYISOCYANURATE INSULATION SLOPE TO SCUPPER 1/4" / FT.
 - E EPDM MEMBRANE
 - F FILTER FABRIC
 - G SEALANT
 - 07 62 00.A METAL CLAD WEATHER BARRIER
 - B FLASHING MEMBRANE
 - C STAINLESS STEEL SILL FLASHING WITH UPTURNED EDGE
 - D 20 GAUGE STAINLESS STEEL CONTINUOUS INTERNAL GUTTER
 - E STAINLESS STEEL COVER FLASHING
 - F 2 PIECE STAINLESS STEEL SNAP FLASHING W/ UPTURNED EDGE INBOARD OF STOREFRONT SYSTEM
 - G STAINLESS STEEL CAP FLASHING WITH HEIMED EDGE BELOW PRECAST
 - H CLEAT SIMILAR TO DETAIL A1-A6/23
 - J STAINLESS STEEL SCUPPER AND 3" DOWNSPOUT, PAINT COLOR #1 (DARK)
 - K STAINLESS STEEL SCUPPER FLANGE
 - L STAINLESS STEEL FLASHING W/ UPTURNED EDGE INBOARD OF BRICK, HEIM EDGE AND EXTEND ONTO FORMED ALUMINUM COPING
 - M 1/2 X 1/2 STAINLESS STEEL HARDWARE CLOTH DEBRIS SCREEN
 - 07 81 00.A SPRAYED-ON FIREPROOFING
 - 07 92 00.A EXTERIOR SEALANT
 - B INTERIOR SEALANT
- Division 08 Openings**
- 08 41 43.A ALUMINUM FRAMED STOREFRONT
 - 08 63 00.A METAL FRAMED SKYLIGHT
 - B SKYLIGHT SUPPORT BRACKET BY SKYLIGHT MANUFACTURER
 - C ALUMINUM FLASHING, SAME COLOR AND FINISH AS SKYLIGHT EXTRUSIONS
- Division 09 Finishes**
- 09 21 00.A GYPSUM WALLBOARD
 - B 1/2" EDGE BEAD
 - C 25 GAUGE CONT. ANGLE
 - D 1 1/2" DEEP VERTICAL FURRING CHANNELS AT 1'-4" O.C.
 - E 20 GAUGE CONT. ANGLE
 - F 250S125-18 FRAMING AT 1'-4" O.C.
 - G 400S125-18 FRAMING AT 1'-4" O.C.
 - H 20 GAUGE CONT. BRACE FORMED CLOSURE
 - J STAND-OFF CLIP FOR FIREPROOFING CLEARANCE
 - K 162S125-18 CLIP
 - L STUD CLIP
 - M 800S162-18 FRAMING AT 1'-4" O.C.
- Division 11 Equipment**
- 11 24 20.A DAVIT WITH STAINLESS STEEL FLASHING AND SEALANT TO PROVIDE WEATHER TIGHT PENETRATION THROUGH INTERNAL GUTTER

- GENERAL NOTES**
- A. SEE DRAWINGS A6.30 AND A6.31 FOR CHAPEL INTERIOR DETAILS
 - B. SEE DRAWINGS A5.03 AND A6.21 FOR CHAPEL EXTERIOR DETAILS