

MATERIAL LEGEND

Division Ø3 Concrete 03 30 00,A CAST IN PLACE COCNRETE COLUMN, SEE STRUCTURAL

B CONCRETE JOIST WHERE OCCURS, SEE STRUCTURAL

Division Ø5 Metals

05 12 00 A STRUCTURAL STEEL W' SHAPE, SEE STRUCTURAL B STRUCTURAL STEEL 'HSS' SHAPE, SEE STRUCTURAL

Division Ø7 Thermal & Moisture Protection

B (2) TWO LAYERS 5/8 IN. TYPE 'X' GYPSUM BD.

E (2) TWO #8 SCREWS TO EACH STUD TO RUNNER F SHAFTWALL 'J' RUNNER, DO NOT ATTACH STUDS, GYPSUM BOARD OR SHAFTLINER TO TOP TRACK.

J (2) TWO 4005 162-33. EXTEND TO CORNER OR INTERSECTION, 15'-0" MAX. SPAN K *8 SCREWS AT 2'-8" STAGGERED CENTERS AND TOW

L .145 DIAMETER POWDER DRIVEN FASTENER CENTERED

Division 10 Specialties 10 44 00.A RECESSED NON-RATED 2-1/2 IN. FIRE DEPARTMENT B RECESSED FIRE-RATED 2-1/2 IN. FIRE DEPARTMENT VALVE CABINET

Division 15 Mechanical

15 00 00.A CLEAR FLOOR OPENING FOR MECHANICAL SHAFT C 2-1/" FIRE DEPARTMENT VALVE WITH CAP AND CHAIN

、PENETRATIONS, SLEEVE(G) PER MEP, MIN. ½ IN. CLR. @ JOISTS, BEAMS W/O STRUCTURAL ENGINEER APPROVAL DIST BELOW, SEE STRUCTURAL FOR SIZE, REINF.

A7

24

(03) OUTLINE OF CONCRETE COLUMN BELOW.