

A  
B  
C  
D  
E

A  
B  
C  
D  
E

- FLOOR FRAMING NOTES**
- COORDINATE ALL DIMENSIONS WITH ARCHITECTURAL DRAWINGS.
  - TYPICAL TOP OF CONCRETE ELEVATION, T.O.C. = 313'-3" UNO FOR EXACT LOCATION OF SLAB ELEVATION CHANGES REFER TO THE ARCHITECTURAL PLANS.
  - TYPICAL TOP OF STEEL ELEVATION, T.O.S. = 312'-4 3/4" UNO [x'-x"]
  - INDICATES MECHANICAL UNITS. SEE PLAN FOR MAXIMUM ALLOWED HEIGHT
  - INDICATES WIDE FLANGE COLUMN LOCATION AND ORIENTATION. SEE SHEET S3.50 FOR COLUMN SCHEDULE.
  - INDICATES SPAN DIRECTION FOR METAL DECK FOR TYPICAL METAL DECK DETAILS SEE 54.40 & 54.41.
  - INDICATES PENETRATION IN FLOOR/ROOF STRUCTURE. SEE 54.40 & 54.41 FOR TYP. REQUIREMENTS @ PENETRATIONS. FOR SLAB EDGE LOCATION SEE ARCH. FOR ADDITIONAL OPENINGS SEE ARCHITECTURAL, MECHANICAL & ELECTRICAL.
  - SEE SHEETS 54.50 AND 54.51 FOR TYPICAL STEEL DETAILS.
  - NON-STRUCTURAL STUD WALLS ARE NOT SHOWN. FOR LOCATION SEE ARCHITECT.
  - BEAM SPACING ALONG GIRDERS ARE AT EQUAL SPACES BETWEEN COLUMNS, OR DIMENSION POINTS UNO.
  - INDICATES THE TOTAL QTY. OF 3/4" DIA. SHEAR STUDS. FOR SHEAR STUD LENGTH AND SPACING SEE 10/54.40
  - INDICATES THE BM/GIRDER CAMBER IN INCHES. INDICATES BM/GIRDER SIZE.
  - INDICATES A REQUIRED TYPICAL DETAIL
  - INDICATES THE BEAM T.O.S. ELEVATION WITH REFERENCE TO THE TYPICAL T.O.S. ELEVATION. DIMENSIONS AT BOTH ENDS OF THE BEAM INDICATES A SLOPING MEMBER.
  - INDICATES STRUCTURAL WALL BELOW EXTENDING TO FLOOR STRUCTURE.
  - FOR CONCRETE CURB & HOUSEKEEPING PAD LOCATIONS AND SIZES SEE ARCHITECTURAL, MECHANICAL & ELECTRICAL. FOR TYP. DETAIL SEE 0/54.40.
  - SEE SHEET 54.51 FOR TYPICAL ELEVATOR FRAMING DETAILS
  - INDICATES CONCRETE BEAM SEE 54.20 FOR SCHEDULE & DETAILS.
  - INDICATE CONCRETE JOIST SEE 54.20 FOR SCHEDULE & DETAILS.
  - INDICATES POST-TENSIONED GIRDER SEE 54.10, 54.11, 54.11A & 54.12 FOR SCHEDULE & DETAILS.
  - INDICATES SPECIAL METAL STUD WALL TYPE. FOR SCHEDULE SEE 6/55.61. ALL WALLS NOTED SHALL BE CONSTRUCTED WITH NO GAP AT TOP OF WALL. FOR SPECIAL METAL STUD WALL TYPICAL DETAILS SEE 1/55.61 & 0/55.61.

