

1 SURFACE DRAINAGE PAVING SYSTEM  
COLORED CONCRETE PAVING w/ 2% SLOPE TO DRAIN  
a) WATERPROOFING MEMBRANE UP-3  
b) SLOPED TOPPING SLAB - 2% MIN. SEE DETAIL 2A/11.

2 OPEN JOINT PAVING SYSTEM  
FEDERAL SUPPORTED STONE PAVING STONE (S.L.D. FOR STONE SIFEC AND FINISH)  
a) WATERPROOFING MEMBRANE UP-3  
b) SLOPED TOPPING SLAB - 2% MIN. SEE DETAIL 2A/11.

3 FOR ORAINS AND FIELD SEE A10/ AND A10/2.

4 POROUS PAVING SYSTEM  
CUSHIONED CONCRETE SAND COMPORESSED GRANITE  
a) COMPACTED SUBGRADE  
b) WATERPROOFING MEMBRANE UP-3  
c) SLOPED TOPPING SLAB - 2% MIN. SEE DETAIL 2A/11.

5 FOR ORAINS AND FIELD SEE A10/ AND A10/2.

6 LANDSCAPED PLAZA AND PLANTER SYSTEM  
a) PROJECTION COURSE/ROOT BARRIER  
b) DRAINAGE COMPOSITE  
c) WATERPROOFING MEMBRANE UP-3  
SEE DETAIL 3A/11.

### GENERAL NOTES

1. REFER TO A101 AND A102 FOR BUILT-UP SLAB/CURB EXTENT AND DRAIN LAYOUT INFORMATION.
2. REFER TO LANDSCAPE DRAWINGS FOR EXTERIOR OUTLETS
3. EXTERIOR LIGHT FIXTURE INFORMATION.
  - REFER TO LANDSCAPE DRAWINGS FOR LUMINAIRE LOCATION AND LOCATION
  - REFER TO DRAWINGS FOR WATER FEATURE FIXTURE LAYOUT.
  - REFER TO ARCHITECTURAL DRAWINGS FOR HARDWARE FIXTURE POSITIONS. SEE ELEVATIONS FOR LIGHT LOCATION.
4. FOR PLANTER WALL AND WATERFEATURE AREA USE REINFORCED CONCRETE BUILT UP SLAB S.D. w/ CRYSTALLINE WATERPROOFING ADMIXTURE

TYPICAL PAVER PATTERN

ST-10' (BH) STONE FIELD PAVERS (TYP.) 16' x 33'

ST-10' (SB) STONE ACCENT PAVERS (TYP.) 8' x 32'

LIGHT FIXTURE LEGEND

|    |                         |
|----|-------------------------|
| □  | RECESSED WALL LUMINAIRE |
| ▲  | LANDSCAPE UPLIGHT       |
| ⊕  | BOLLARD LIGHT           |
| ⊗  | WATER FEATURE UPLIGHT   |
| ⊕⊗ | DRIVEWAY/ WALKWAY LIGHT |
| ○  | POLE MOUNTED LUMINAIRE  |
| ●  | POLE MOUNTED DOWNLIGHT  |

FOR ALL EXTERNAL HARD AND SOFT SCAPE FINISHES  
SEE LANDSCAPE ARCHITECTS DRAWINGS

TONE INDICATES  
EXTENT OF PHASE  
SUBMITTED UNDER  
SEPARATE  
APPLICATION

