

KODIAK AIRPORT

KODIAK, ALASKA


KODIAK AIRPORT RSA EXTENSION

PROJECT No. 53587

AIRPORT IMPROVEMENT PROGRAM
No. 3-02-0158-017-2014

PROJECT No. 57474
AIRPORT IMPROVEMENT PROGRAM
No. 3-02-0158-01X-201

CENTRAL REGION AS-ADVERTISED APRIL, 2014



DATE 3/27/2014

JOEL ST. AURIN, P.E.

DIRECTOR OF DERIGNIAND CONSTRUCTION

APPROVED

MENNETH M. MORTON, P.E.

APPROVED

WOLFGANG E. JUNGE, P.E.

DATE 3/25/14

DESIGN SECTION CHIEF

APPROVED

MORGAN MERRUTT, P.E.

PROJECT MANAGER

PROJECT MANAGER

VICINITY MAP

T 28 S, R 20 W SEC. 14, 15, 15, 22 & 23 SEWARD MERIDIAN U.S.G.S. KODIAK (C-2, 0-2), ALASKA

250	LE.		4524	
20	A O DI	*	74	
	J.	P	ealer	
THE STATE OF THE S	Old Car	Greetey -10563	1 8	
1,642	AND AND	ESSIGNA	0.2	
PREPARED	BY-	HDD	Ataska	lan e


BY	DATE	REVISION
	BV	By DATE

STATE OF ALASKA
DEPARTMENT OF TRANSPORTATION
AND PUBLIC FACILITIES
CENTRAL REGION

KODIAK AIRPORT KODIAK, ALASKA

TITLES, SIGNATURES, LOCATION MAP

SHEET:
A1 OF A1
AS-BUILT SHEET:



KODIAK AIRPORT


KODIAK, ALASKA

KODIAK AIRPORT RSA EXTENSION

PROJECT No. 53587

AIRPORT IMPROVEMENT PROGRAM

No. 3-02-0158-017-2014



NOT TO SCALE

CONCUR

JOEL ST. AUSIN, P.E.

DATE 3/27/2014

DIRECTOR OF DESIGN AND CONSTRUCTION

APPROVED

MENNETH M. MORTON, P.E.

APPROVED

WOLFGANG E. JUNGE, P.E.

APPROVED

APPROVED


MORGAN MERRITT, P.E.

DATE 3/24/14

/PROJECT MANAGER

VICINITY MAP

T 28 S, R 20 W SEC. 14, 15, 16, 22 & 23 SEWARD MERIDIAN U.S.G.S. KODIAK (C-2, D-2), ALASKA



DEPARTM AND DATE REVISION

STATE OF ALASKA
DEPARTMENT OF TRANSPORTATION
AND PUBLIC FACILITIES
CENTRAL REGION

KODIAK AIRPORT
KODIAK, ALASKA
KODIAK AIRPORT RSA EXTENSION, 2014
PROJECT No. 5-3587
AIP No. 3-02-0158-017 :2014
TITLES, SIGNATURES, LOCATION MAP
AND VICINITY MAP

SHEET:


1 OF 39


AS-BUILT SHEET:


INDEX		INDEX CONT'D		APPENDIX DRAWINGS		
SHEET TITLE	SHEET No.	SHEET TITLE	SHEET No.	SHEET TITLE	SHEET No	
BASIC BID		MARKING REMOVAL PLAN RUNWAY 18-36	33	APPENDIX B	A E M COMPANIA A COMP	
		MARKING PLAN RUNWAY 18-36	34	SURVEY CONTROL	AB1	
TITLE, SIGNATURES, LOCATION MAP AND VICINITY MAP	1	MARKING PLAN RUNWAY END 25	35			
INDEX	2	RUNWAY MARKING DETAILS	36	APPENDIX D		
LEGEND AND ABBREVIATIONS	3	TAXIWAY MARKING DETAILS	37	PHASING PLAN		
ESTIMATED QUANTITIES AND ESTIMATING FACTORS	4	SEGMENTED CIRCLE AND WIND CONE PLAN	38	PHASE 1A	AD1 OF 15	
PROJECT LAYOUT PLAN	5	SEGMENTED CIRCLE DETAILS		PHASE 1B	AD2 OF 15 AD3 OF15	
RUNWAY 25 TYPICAL SECTION			39	PHASE 2A	AD4 OF15	
		RUNWAY 25 TEMPORARY LIGHTING PLAN	D1	PHASE 2B	AD5 OF 15	
RUNWAY 25 TYPICAL SECTION	7	RW 36 AND TW A LIGHTING DEMOLITION PLAN	D2	PHASE 2C	AD6 OF 15	
RUNWAY 25 TYPICAL SECTIONS	8	RW 18 LIGHTING DEMOLITION PLAN	D3			
RUNWAY 36 TYPICAL SECTIONS	9	RUNWAY 36 LIGHTING PLAN	E1	SAFETY PLAN		
RUNWAY 36 TYPICAL SECTIONS	10	RUNWAY 18 LIGHTING PLAN AND WIND CONE PLAN	E2	SAFETY PLAN NOTES	AD7 OF15	
RUNWAY 36 TYPICAL SECTIONS	11	AIRFIELD LIGHTING DETAILS	E3	OVERVIEW	AD8 OF 15	
RUNWAY 36 TYPICAL SECTIONS	12	SIGN SCHEDULE DETAILS	principal and the second	PHASE 1A PHASE 1B	AD9 OF 15	
SHORE PROTECTION (ARMOR STONE) TYPICAL SECTIONS	13	WIND CONE DETAILS	E4	PHASE 2A	AD10 OF 15 AD11 OF15	
SHORE PROTECTION (CAU) TYPICAL SECTION AND DETAILS	14		E5	PHASE 2B	AD12 OF 15	
		TEMPORARY LIGHTING DETAILS AND NOTES	E 6	PHASE 2C	AD13 OF 15	
AXIWAY B TYPICAL SECTION	15	REIL DETAILS	E7	TEMPORARY MARKING PLAN	AD14 OF 15	
RUNWAY 25 PLAN AND PROFILE 16		FAA REFERENCE DRAWING REIL WIRING DIAGRAM	E8	DETAILS	AD15 OF 15	
RUNWAY 25 SHORE PROTECTION PLAN AND PROFILE	17	FAA REFERENCE DRAWING REIL WIRING AND DETAILS	E9	마이블리팅 과 하는 1일 시작되는 중 중요한		
RUNWAY 36 PLAN AND PROFILE	18	FAA REFERENCE DRAWING VASI PLAN VIEW, ELEVATION, & DETAILS	E10	로마스 보고 있는 사람은 하다 하다 하다.		
RUNWAY 18 PLAN AND PROFILE	19	FAA REFERENCE DRAWING VASI FOUNDATION PLAN, SECTION, & DETAILS	E11			
TAXIWAY B PLAN AND PROFILE	20	FAA REFERENCE DRAWING ELECTRICAL SCHEMATIC DIAGRAM	E12			
RUNWAY 25 RSA GRADING PLAN	21	FAA REFERENCE DRAWING GROUNDING PLAN & TRENCH DETAIL	E13	그렇다 많아 날아를 가는 맛을 받았다.		
AXIWAY A AND B GRADING PLAN	22	FAA REFERENCE DRAWING REIL DETAILS	E14	마루 시스 중 하는데 아니라 막다 보다고 하는데 되었다.		
RUNWAY 25 SERVICE ROAD PLAN AND PROFILE	23	FAA REFERENCE DRAWING REIL DETAILS	E15	STANDARD DRA	AWINGS	
RUNWAY 36 SERVICE ROAD PLAN AND PROFILE	24	FAA REFERENCE DRAWING REIL DETAILS			AVVIINGO	
AXIWAY C PAVEMENT REPAIR	25	FAA REFERENCE DRAWING REIL DETAILS	E16	SHEET TITLE	SHEET No.	
UNWAY 25 EMAS PLAN VIEW			E17	SYMBOLS	A-1	
	26	FAA REFERENCE DRAWING REIL DETAILS	E18	CULVERT PIPE AND ARCH INSTALLATION DETAILS	D-01.02	
UNWAY 25 EMAS PROFILE VIEW	27	FAA REFERENCE DRAWING REIL DETAILS	E19	SEDIMENT CONTROL SYSTEM (SILT FENCE)	E-13.00	
UNWAY 25 EMAS SECTION VIEW	28					
UNWAY 18 EMAS PLAN VIEW	29			[일본 10명 : 사람이 사용하다 [1] 20 12 2		
UNWAY 18 EMAS PROFILE VIEW	30	ANCILLARY DRAWIN	GS	성화하는 경기 없었다. 중국 리미얼 모양을		
UNWAY 18 EMAS SECTION VIEW	31	SHEET TITLE	SHEET No.			
UNWAY 25 & RUNWAY 18 EMAS DETAILS	32	OF A Conne				
		A 9 10. Solved Country CC-10545	D	EPARTMENT OF TRANSPORTATION KODIAK AIRPO	DIAK AIRPORT ODIAK, ALASKA ORT RSA EXTENSION, 2014 DATE: 3/26/2014 SHEET:	
		PREPARED BY: HDR Alaska, Inc. BY DATE RET	VISION	PR	ORT RSA EXTENSION, 2014 OJECT No. 53587 3-02-0158-017-2014 INDEX	


LEGE	ND		ABBREVIATIONS	ABBREVIATIONS
DESCRIPTION	EXISTING	PROPOSED		
AIRCRAFT TIE-DOWNS	7		AOA AIRCRAFT OPERATIONS AREA	RT RIGHT OFFSET
BUILDING			ARFF AIRPORT RESCUE FIRE FIGHTING	프를 그 내회 시에 작은 어떻게 돼졌다면 화면하를 하게 되었습니다. 나이 너무의 되었어요?
CONSTRUCTION LICENSE BOUNDARY			하는 맛이들이 그 밥을 내고 있다면 하면 하는데 그는데 그를 모든 어느 때문.	RW RUNWAY
CONTROL BOX			ASDA ACCELERATE STOP DISTANCE AVAILABLE	SD STORM DRAIN
OTCH WITH DRAINAGE FLOW DIRECTION	>-		ATCT AIR TRAFFIC CONTROL TOWER	S.F. SQUARE FEET
DGE OF PAVEMENT			AWOS AUTOMATED WEATHER OBSERVING SYSTEM	SPCD SAFETY PLAN COMPLIANCE DOCUMENT
ENCE	xx-	—x——x——	CABC CRUSHED AGGREGATE BASE COURSE	SS SANITARY SEWER
SEOTEXTILE SEPARATION		GB	CAU CONCRETE ARMOR UNIT	STA STATION
RADE BREAK EASE LOT BOUNDARY			CL CENTER LINE	이 얼마 그 나는 사람이 가게 가게 하면 하는 사람들이 되었다면 하는데 그는 사람들이 되었다.
IEAN HIGH WATER			그는 옷이 살이 어느라 하는데 아마들이 말이 이 없다면 하셨다면 하는데 살아가 되었다.	TODA TAKE OFF DISTANCE AVAILABLE
XISTING GROUND			1lb./cu.ft. POUND PER CUBIC FOOT	TORA TAKE OFF RUN AVAILABLE
BJECT FREE AREA	OFA —		C.S. CONTINGENT SUM	TW TAXIWAY
DBJECT FREE ZONE	—— 0FZ ——	Addition about	CSPP CONSTRUCTION SAFETY PHASING PLAN	OFA OBJECT FREE AREA
PAVEMENT MARKING		2023	C.Y. CUBIC YARD	OFZ OBJECT FREE ZONE
PROJECT EARTHWORK AND GRADING LIMITS			E EASTING	OHE OVERHEAD ELECTRIC
ROPERTY BOUNDARY			ELEV ELEVATION	
EIL	8			UGE UNDERGROUND ELECTRIC
IPRAP / ARMOR OADWAY		HAZY	EMAS ENGINEERED MATERIAL ARRESTING SYSTEM	UGTel UNDERGROUND TELECOMMUNICATIONS
OTATING BEACON	======================================		EOP EDGE OF PAVEMENT	USCG UNITED STATES COAST GUARD
RUNWAY DISPLACED THRESHOLD LIGHT		0	FASBC FOAMED ASPHALT STABILIZED BASE COURSE	VASI VISUAL APPROACH SLOPE INDICATOR
RUNWAY EDGE LIGHT		☆	FOD FOREIGN OBJECT DEBRIS/ FOREIGN OBJECT DAMAGE	Wx WEATHER
RUNWAY FLUSH MOUNT LIGHT		•	GB GRADE BREAK	[18]
RUNWAY PROTECTION ZONE RUNWAY SAFETY AREA	RPZ			(38) - [118] 요즘 그는 그는 이 등을 하는 사람들은 사람들을 받는데
RUNWAY THRESHOLD MARKERS	0000	0000	- III ' ' 1111년에 대한 시대 등록 하고 있는 경기 등록 하고 있다.	통 이 - [중요] (1) 보고 하고 있다. 루션 (2) 그렇게 있는 12 (2) 그는 12 (2) 다른 10 (2)
SIGN		-0-	HMA HOT MIXED ASPHALT	[일] - [[[일일 : [[인명]] : [[일 : [[일 : []]]] [[일 : []]] [[일 : []]] [[일 : []] [[일 : []]] [[일 : []] [[]] [[] [[]] [[]] [[] [[]] [[] [[]] [[]] [[] [[]] [[]] [[] [[]] [[]] [[]] [[] [[]] [[] [[]] [[]] [[] [[]] [[] [[]] [[]] [[] [[]] [[]] [[] [[]] [[] [[]] [[] [[]] [[] [[]] [[] [[]] [[] [[]] [[] [[] [[]] [[] [[] [[]] [[]
SLOPE VALUE AND DIRECTION		X.XXX	LDA LANDING DISTANCE AVAILABLE	[문문 [문화사람(사람) 항상 기본 10년 10년 10년 12년 12년 12년 12년 12년 12년 12년 12년 12년 12
SPOT ELEVATION TOE OF SLOPE		X.XX	L.F. LINEAR FOOT	없는 이 이 사람들을 하고 있다면 하는 사람들은 사람들이 되었다면 보다.
FILL			L.S. LUMP SUM	시 :
CUT			LT LEFT OFFSET	이는 - [마음아음말림아음아음마일] 알아라고아와 나타를 먹었다.
ASI	۵۵		MHW MEAN HIGH WATER	DETAIL NUMBER
VIND CONE UNLIGHTED	1		그 1000 - 44 이렇게 하시다면 있을 데 있을 맛있다면 하실 말을 살았다.	그리 - [19] [6명 20] [18] [2] - 유지 (18] [18] [18] [18] [18] [18]
	54	4-5	MPH MILES PER HOUR	SHEET WHERE DETAIL IS LOCATED
IND CONE AND SEGMENTED CIRCLE	r ();	450	N NORTHING	DETAIL MARKER
*	35		N.T.S. NOT TO SCALE	SECTION LETTER
			RAP RECYCLED ASPHALT PAVEMENT	FLAG INDICATES DIRECTION OF SECTION CUT
			RPZ RUNWAY PROTECTION ZONE	SHEET WHERE SECTION
			RSA RUNWAY SAFETY AREA	SECTION CUT MARKER
				SECTION COT MARKER
				날이 다 나는 사람들은 사람들이 살아 되었다. 유리를 하고 있는 것이 없는데 없었다.
			Control of A Control	Pr
			7.49 H	KODIAK AIDDODE INAT-
			3. Und Coulty 5	STATE OF ALASKA DEPARTMENT OF TRANSPORTATION KODIAK AIRPORT KODIAK ALASKA KODIAK AIRPORT RSA EXTENSION, 2014 SHEET:
			ANY ESSION	AND DURI IC FACILITIES PROJECT No. 53587
			PREPARED BY: HDR Alaska, Inc. BY DATE REVISION	CENTRAL REGION LEGEND AND ARRESTATIONS


ESTIMATED					QUANTITIES			ESTIMATING FACTORS		
No.	ITEM	UNIT (QUANTITY	No.	ITEM	UNIT	QUANTITY	ITEM DESCRIPTION	ESTIMATING F	ACTO
D-701a(1)	PE PIPE, 18"	LF.	50	P-152i(1)	BORROW (<6% NO. 200)	TON	505000	HOT MIX ASPHALT	150 lb./cu.ft.	
D-701a(2)	PE PIPE, 24"	L.F.	54	P-152i(2)	BORROW (<10% NO. 200)	TON	675800	ASPHALT CEMENT	5.5%	
G-100a	MOBILIZATION AND DEMOBILIZATION	L.S.	ALL REQ'D	P-152r	SUBGRADE PREPARATION	S.Y.	9600	CRUSHED AGGREGATE BASE COURSE	145 lb./cu.ft.	Alber
G-115a	WORKER MEALS AND LODGING, OR PER DIEM	L.S.	ALL REQ'D	P-154b	SUBBASE COURSE	TON	73500	SUBBASE	142 lb./cu.ft.	
G-130a	FIELD OFFICE	L.S.	ALL REQ'D	P-157a	EROSION, SEDIMENT, AND POLLUTION CONTROL ADMINISTRATION	L.S.	ALL REQ'D	ARMOR STONE	1.6 ton/cu.yd.	1433.5
G-130b	FIELD LABORATORY	L.S.	ALL REQ'D	P-157b	TEMPORARY EROSION, SEDIMENT, AND POLLUTION CONTROL	c.s.	ALL REQ'D	UNDERLAYER STONE	1.6 ton/cu.yd.	(fire a file
G-130g	NUCLEAR TESTING EQUIPMENT STORAGE SHED	EACH	1	P-157f	WITHHOLDING	C.S.	ALL REQ'D	SLOPE LINING	130 lb/cu.ft.	
G-130h	STORAGE CONTAINER	EACH	1	P-157g	SWPPP MANAGER	LS.	ALL REQ'D			4. Spring
G-130j	ENGINEERING COMMUNICATIONS	C.S.	ALL REQ'D	P-161b	RECYCLED ASPHALT PAVEMENT	C.Y.	2600			
G-131a	ENGINEERING TRANSPORTATION (TRUCK)	EACH	6	P-162a	PAVEMENT COLD PLANING	S.Y.	3200			
G-135a	CONSTRUCTION SURVEYING BY THE CONTRACTOR	LS.	ALL REQ'D	P-165a(1)	REMOVAL OF STRUCTURES (RSA EXTENSION)	L.S.	ALL REQ'D			
G-135b	EXTRA THREE PERSON SURVEYING PARTY	HOUR	50	P-181a	CONCRETE ARMOR UNITS (2.65 TON)	EACH	2600			
G-150a	EQUIPMENT RENTAL, DOZER (70hp MINIMUM)	HOUR	50	P-185a	PRIMARY ARMOR STONE (PA-12000)	TON	81700			
G-200a	CONTRACTOR QUALITY CONTROL PROGRAM	L.S.	ALL REQ'D	P-185b	UNDERLAYER STONE (U-700)	TON	41000			
G-300a	CPM SCHEDULING	L.S.	ALL REQ'D	P-189b	GABIONS (STAINLESS STEEL)	C.Y.	940			
G-700a	AIRPORT FLAGGER	C.S.	ALL REQ'D	P-209b	CRUSHED AGGREGATE BASE COURSE	TON	5400			
G-710a	HIGHWAY TRAFFIC MAINTENANCE	LS.	ALL REQ'D	P-401a	HOT MIX ASPHALT, TYPE II, Class A	TON	5300			
G-710b	HIGHWAY FLAGGER	C.S.	ALL REQ'D	P-401b	HOT MIX ASPHALT PRICE ADJUSTMENT	C.S.	ALL REQ'D			
G-710c	HIGHWAY TRAFFIC PRICE ADJUSTMENT	C.S.	ALL REQ'D	P-401c	ASPHALT CEMENT, PG 52-28	TON	295			
G-710d	HIGHWAY TRAFFIC CONTROL	C.S.	ALL REQ'D	P-555a(1)	INSTALL EMAS BED (RUNWAY 7)	L.S.	ALL REQ'D			
G-715c	WILDLIFE MONITORING	c.s.	ALL REQ'D	P-555a(2)	INSTALL EMAS BED (RUNWAY 36)	L.S.	ALL REQ'D			
L-100c(1)	HIGH INTENSITY RUNWAY EDGE AND THRESHOLD LIGHT, L-862 and L-862E	EACH	21	P-556a	EMAS SNOW REMOVAL EQUIPMENT (TYPE I)	EACH	1			
L-100c(2)	HIGH INTENSITY RUNWAY EDGE AND THRESHOLD LIGHT LENS, L-862 and L-862E	EACH	3	P-603a	TACK COAT, STE-1	TON	5			
L-100e	TAXIWAY EDGE LIGHT, L-861T	EACH	22	P-620c	RUNWAY AND TAXIWAY PAINTING	LS.	ALL REQ'D			
L-100h	REMOVE RUNWAY AND TAXIWAY LIGHT	EACH	41	P-620f	PAINTED MARKING REMOVAL	L.S.	ALL REQ'D			
100n	AIRPORT SIGN, Type L-858	EACH	4	P-621b	SAW-CUT GROOVES	L.S.	ALL REQ'D			
100r	TEMPORARY RUNWAY LIGHTING SYSTEM	L.S.	ALL REQ'D	P-640b	SEGMENTED CIRCLE (PANEL TYPE)	L.S.	ALL REQ'D			
100ap	SPARE PARTS	L.S.	ALL REQ'D	P-670b	FLASHER UNIT FOR TIMBER BARRIER	EACH	75			
107a	8-FOOT LIGHTED WIND CONE, IN PLACE	EACH	1	P-670c	FLAG	EACH	75			
	UNDERGROUND CABLE #8 AWG, COPPER, 5KV FAA	L.F.	3250	P-671c	ILLUMINATED RUNWAY CLOSURE MARKER	EACH	2			
	TYPE "C", L-824 # 6 BARE COPPER GROUND CONDUCTOR	L.F	2850	P-684a	FLOATING SILT CURTAIN	LF.	4100			
	GROUND ROD	EACH	5							
	2-INCH RIGID STEEL CONDUIT	L.F.	435							
	2-INCH PE CONDUIT	L.F.	2250		armining the					
	FOUNDATION AND UTILITIES FOR FAA EQUIPMENT	L.S.	ALL REQ'D		OF ALABAM					
					Justine 1			STATE OF ALASKA	KODIAK AIRPORT	DATE: 3/26/20
5	CLEARING	L.S.	ALL REQ'D		9414		DE	PARTMENT OF TRANSPORTATION	KODIAK, ALASKA KODIAK AIRPORT RSA EXTENSION, 2014 PROJECT No. 53587	SHEET:
2-152ak	SLOPE LINING	TON	500		PREPARED BY: HDR Alasko, Inc. BY DATE	REVISION		AND PUBLIC FACILITIES CENTRAL REGION	AIP No. 3-02-0158-017-2014 ESTIMATED QUANTITIES	AS-BUILT SHI





























NOTE

1. FROM STATION 179+72 TO STATION 180+22 UNDERLAYER THICKNESS CONTINUOUSLY TRANSITIONS FROM 5 TO 3.

N.T.S.

- CREST ELEVATION OF CONCRETE ARMOR UNITS SHALL MATCH ADJACENT EDGE OF RSA EMBANKMENT CREST ELEVATION.
- UNDERLAYER STONE MEDIAN STONE WEIGHT IS 700 Ibs. REFER TO SPECIFICATION SECTION "ITEM P-185 ARMOR STONE" FOR ADDITIONAL GRADATION AND STONE REQUIREMENTS.
- 4. ARMOR STONE SHALL BE PLACED AND SPREAD IN SUCH A MANOR THAT THE VARIOUS STONE SIZES PRODUCE A RELATIVELY UNIFORM OUTER SURFACE AND A COMPLETED LAYER THAT IS A REASONABLY WELL GRADED COMPACT MASS OF ROCK.
- UNDERLAYER STONE PLACEMENT SHALL MAXIMIZE CONTACT BETWEEN INDIVIDUAL STONES ON ALL SIDES WITH EACH STONE HAVING AT LEAST THREE POINTS OF CONTACT WITH OTHER STONES.
- REFER TO SPECIFICATION SECTION "ITEM P-181 CONCRETE ARMOR UNITS" FOR ADDITIONAL CONCRETE ARMOR UNITS REQUIREMENTS.
- 7. ELEVATIONS SHOWN IN ARE IN FEET, NAVD '88.

TIDAL DATA:

TIDAL DATA RETRIEVED FROM THE NOAA CO-OPS WEBSITE AT ADDRESS http://co-ops.nos.noad.gov/station_retrieve.shtml?type=bench+mark+data+sheets for 9457292 KODIAK ISLAND, AK. (WOMENS BAY) PUBLICATION DATE: 09/12/2007 TIME PERIOD; JAN. 2002 - DEC. 2006

THE NOAA TIDAL DATA WATER LEVELS ADJUSTED TO NAVD88 = 0.0 FEET AS FOLLOWS:


EXTREME HIGH WATER	EHW	+14.06	12/31/198
MEAN HIGH WATER	MHW	+8.63	
MEAN HIGHER HIGH WATER	MHHW	+9.53	
MEAN SEA LEVEL	MSL	+5.25	
MEAN TIDE LEVEL	MTL	+5.25	
MEAN LOW WATER	MLW	+1.87	
MEAN LOWER LOW WATER	MLLW	+0.76	
NAVD88 DATUM ORIGIN		0.00'	
EXTREME LOW WATER	ELW	-2.43	1/12/2005
이 마이에 있는 사람이 되었다. 그렇게 하지 않는데 그리고 모르다.			


STATE OF ALASKA
DEPARTMENT OF TRANSPORTATION
AND PUBLIC FACILITIES
CENTRAL REGION

KODIAK AIRPORT
KODIAK, ALASKA
KODIAK AIRPORT RSA EXTENSION, 2014
PROJECT NO. 35387
AIP NO. 3-02-0158-017-2014
SHORE PROTECTION (CAU)

DATE: 3/18/2014 SHEET: 14 OF 39 AS-BUILT SHEET:







TAXIWAY B AT RUNWAY 36 THRESHOLD

N.T.S. NOT SYMMETRIC ALONG CENTERLINE

NOTES

- UNCLASSIFIED EXCAVATION WILL NOT BE MEASURED FOR PAYMENT BUT CONSIDERED SUBSIDIARY TO OTHER ITEMS.
- 2. ORIGINAL GROUND MAY VARY FROM THAT DEPICTED IN TYPICAL SECTIONS.
- 3. IF RAP QUANTITIES ARE INSUFFICIENT CABC USED AS DIRECT REPLACEMENT INCH FOR INCH




General Comments	
01/1/3. Greeley () 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	
Noted Communication of the Com	
0.7.611003	
	77


STATE OF ALASKA
DEPARTMENT OF TRANSPORTATION
AND PUBLIC FACILITIES
CENTRAL REGION


KODIAK AIRPORT KODIAK, ALASKA KODIAK AIRPORT RSA EXTENSION, 2014 PROJECT No. 53587 AIP No. 3-02-0158-017-2014 TAXIWAY B


TYPICAL SECTION


SHEET: 15 OF 39 AS-BUILT SHEET:












HMA EXTENSION DETAIL N.T.S.

COMPACTION REQUIREMENTS					
	UNDER PAVED AREAS	UNDER UNPAVED AREAS	IN WATER		
HOT MIX ASPHALT	95%	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Tarabata (* 🛂 (*)		
RAP	98%	98%	Park and L ike		
SUBBASE	100%	95%			

NOTE:

- 1. VERTICAL DATUM NAVD 88.
- 2. REFER TO RUNWAY MARKING PLANS FOR STRIPING AND END IDENTIFIERS.
- 3. REFER TO SURVEY CONTROL SHEET FOR PROJECT LAYOUT.





KODIAK AIRPORT KODIAK, ALASKA KODIAK AIRPORT RSA EXTENSION, 2014 PROJECT No. 53587 AIP No. 3-02-0158-017-2014


RUNWAY 18


3/18/2014 19 of 39 AS-BUILT SHEET: OF


STATE OF ALASKA **DEPARTMENT OF TRANSPORTATION** AND PUBLIC FACILITIES **CENTRAL REGION** REVISION























EMAS SECTION VIEW NOTES:

- 1. EMAS BED WIDTH TOLERANCE IS -0.1% TO +1%
- ALL BLOCKS ARE 4.0' X 4.0' X THICKNESS SHOWN. A
 JET BLAST COATING IS APPLIED PRIOR TO SHIPPING. FOR
 EASE OF IDENTIFYING BLOCKS DURING CONSTRUCTION, NOMINAL VALUES ARE USED.
- 3. BLOCKS INSTALLED WITH A 0.05' GAP (#1/2")
- 4. SEE EMAS PLAN VIEW SHEET 26 FOR CROSS SECTION REFERENCES.




PREPARED BY: Engineered Arresting Systems Corporation


BY DATE REVISION


STATE OF ALASKA **DEPARTMENT OF TRANSPORTATION** AND PUBLIC FACILITIES CENTRAL REGION

KODIAK AIRPORT
KODIAK, ALASKA
RUNWAY SAFETY AREA EXTENSION
PROJECT No. 53587
AIP No. 3-02-0158-017-2014 RUNWAY 25 EMAS SECTION VIEW

3/18/2014 28 of 39 AS-BUILT SHEET: OF







EMAS SECTION VIEW NOTES:

- 1. EMAS BED WIDTH TOLERANCE IS -0.1% TO +1%
- ALL BLOCKS ARE 4.0' X 4.0' X THICKNESS SHOWN. A
 JET BLAST COATING IS APPLIED PRIOR TO SHIPPING, FOR
 EASE OF IDENTIFYING BLOCKS DURING CONSTRUCTION, NOMINAL VALUES ARE USED.
- 3. BLOCKS INSTALLED WITH A 0.05' GAP (≈1/2")
- 4. SEE EMAS PLAN VIEW SHEET 29 FOR CROSS SECTION REFERENCES.



PREPARED BY: Engineered Arresting Systems Corporation


BY DATE REVISION


STATE OF ALASKA DEPARTMENT OF TRANSPORTATION AND PUBLIC FACILITIES **CENTRAL REGION**


KODIAK AIRPORT
KODIAK, ALASKA
RUNWAY SAFETY AREA EXTENSION
PROJECT No. 53587
AIP No. 3-02-0158-017-2014


RUNWAY 18 EMAS SECTION VIEW


3/18/2014 31 of 39 AS-BUILT SHEET: a=



















- STRUCTURAL MEMBERS SHALL BE FASTENED TOGETHER WITH 3/8" X 5" GALVANIZED GRADE 2 STEEL BOLTS WITH NUT AND 2-25¢ WASHERS EACH.
- GUSSET PLATES SHALL BE FASTENED TOGETHER WITH SIX 3/8" X 3" GALVANIZED GRADE STEEL BOLTS.
- 4. PANEL SHALL BE 1/8" THICK ALUMINUM, ASTM B209, PRE PUNCHED 0.5" FOR FASTENERS AS INDICATED IN DRAWING. FASTEN TO STRUCTURAL MEMBERS THROUGH LONGITUDINAL MEMBERS WITH 3/8" X 5" GALVANIZED GRADE 2 STEEL BOLTS WITH 0.5" DIAMETER WASHERS.
- THE GUSSET PLATES SHALL BE FABRICATED FROM 1/4" STEEL PLATE, ASTM A36; GALVANIZED.
- ASSURE EACH PANEL IS RECONSTRUCTED TO THE SAME TOP ELEVATION.




* TOP GUSSET PLATES ONLY


GUSSET PLATE "A" DETAIL





GUSSET PLATE "B" DETAIL



SPLICE PLATE DETAIL







SEGMENTED CIRCLE PANELS

SEGMENTED CIRCLE LAYOUT





0.3				T
I'A				ŀ
				1
Serie Control	\vdash			l
Naska, Inc.	BY	DATE	REVISION	ŀ


STATE OF ALASKA
DEPARTMENT OF TRANSPORTATION
AND PUBLIC FACILITIES
CENTRAL REGION


KODIAK AIRPORT
KODIAK, ALASKA
KODIAK AIRPORT RSA EXTENSION, 2014
PROJECT No. 53587
AIP No. 3-02-0158-017-2014
SEGMENTED CIRCLE
DETAILS


DATE: 3/18/2014 SHEET: 39 OF 39 AS-BUILT SHEET:



















* SECONDARY CONDUCTORS SHALL BE SUBSIDIARY TO L-1DDn AND ND SEPARATE PAYMENT WILL BE MADE.



FRONT VIEW E4 NTS


L-858 SIGN DETAILS





3 CONCRETE BASE SIDE VIEW E4 NTS

CONCRETE BASE PLAN E4



NOTES:

- 1. ALL SIGNS SIZE 2, LED STYLE 2 OR 3, CLASS 2.
- NEW SIGNS AND TRANSFORMERS SHALL BE COMPATIBLE WITH EXISTING 6.6 A CIRCUITS.
- 3. PROVIDE NEW TRANSFORMERS, SECDNDARY WIRING, AND GRDUNDING. TRANSFORMER WATTAGE SIZE PER MANUFACTURER'S SPECIFICATION.
- 4. ATTACH SIGNS TO CONCRETE BASE IN ACCORDANCE WITH MANUFACTURE'S INSTRUCTION.
- 5. THE CONTRACTOR SHALL CERTIFY THE CONCRETE BASE IS CONSTRUCTED TO MEET THE SPECIFICATION P61D.
- 6. BEDDING, BACK FILL AND FINISH GRADE RESTORATION SHALL BE SUBSIDIARY TO THE CONTRACT AND ND SEPARATE PAYMENT WILL BE
- ALL CABLES PASSING THROUGH BASE SHALL HAVE SUFFICIENT SLACK TD ALLDW CONNECTORS TO BE DRAWN 3' ABDVE FINISHED GRADE. ALL CABLES SHALL BE TAGGED.

1	5	ELECTRICAL	CONN	NECTION	DETAIL
1	E4	NTS	*		



		HAIL	PEVISION
nc.	BY	DATE	REVISION
- 1			
- 1			
- 1			
- 1			
- 1	-		

STATE OF ALASKA **AND PUBLIC FACILITIES** CENTRAL REGION

KODIAK AIRPORT KODIAK, ALASKA RUNWAY SAFETY AREA EXTENSION PROJECT No. 53587 AIP No. 3-02-0158-017-2014 SIGN SCHEDULE AND DETAILS


3/18/2D14 E4 DFE19


SIGN No.	SIDE ND.	TYPE	PURPOSE	POWER STYLE	LEGEND COLOR	FACE CDLOR	LEGEND	STATIONING
⟨\$\frac{1}{2}\$. 1	L-858Y	DIRECTION	2	BLACK	YELLOW	^-	R/W 18-36 STA 8+53.66 (1DD'LT)
38	1 1 2	L-858L L-858R L-858Y	LOCATION MANDATORY DIRECTION	2	AETTOM AETTOM	BLACK RED YELLDW	A 36 B	R/W 18-36 STA 8+18.6D (25D'LT)
39>	1 1 2	L-858R L-858L L-858Y	MANDATDRY LOCATION DIRECTION	2	WHITE YELLDW BLACK	RED BLACK YELLDW	36 Å \	R/W 18-36 STA 6+81.98 (25D'LT)
41>	1 1	L-858R L-858L L-858Y	DESTINATION LOCATION DIRECTION	2	BLACK YELLOW BLACK	YELLDW BLACK YELLDW	- 36 B	R/W 18-36 STA 8+53.65 (270'LT)

* NUMBER OF MODULES TO BE DETERMINED BY MANUFACTURER.


DEPARTMENT OF TRANSPORTATION

AS-BUILT SHEET: a





2 LIGHTED WINDCONE DETAIL E5 NTS



 VERIFY ANCHOR BOLT SIZE, BOLT CIRCLE, AND FOUNDATION SIZE WITH MANUFACTURER'S SHOP DRAWINGS.

3 L807 WIND CONE POLE BASE DETAIL





	DATE	REVISION	
BY	-		

STATE OF ALASKA
DEPARTMENT OF TRANSPORTATION
AND PUBLIC FACILITIES
CENTRAL REGION

KODIAK AIRPORT KODIAK, ALASKA RUNWAY SAFETY AREA EXTENSION PROJECT NO. 53587 AIP NO. 3-02-0158-017-2014 WIND CONE DETAILS


DATE: 3/1B/2014 SHEET: E5 OF E19 AS-BUILT SHEET:






TEMPORARY LIGHTING NOTES:

- PROVIDE TEMPORARY THRESHOLD LIGHT BARS AND EDGE LIGHTS IN ACCORDANCE WITH THE PROJECT SAFETY PLAN AND AS DIRECTED BY THE ENGINEER.
- CONSTRUCTION, INSTALLATION, MAINTENANCE AND DEMOLITION OF TEMPORARY EDGE LIGHTS, THRESHOLD LIGHTS AND JUMPERS IS SUBSIDIARY TO PAY ITEM L-100r.
- 3 CONNECT TEMPORARY THRESHOLD LIGHT BARS TO EXISTING EDGE LIGHTS.
- 4. THE TEMPORARY LIGHT FIXTURES SHALL HAVE CORD SETS OF SUFFICIENT LENGTH TO ALLOW CONNECTION TO TRANSFORMER SECONDARY REMOTE FROM THE AREA UNDERNEATH THE L-867B LID FOR THE TEMPORARY THRESHOLD.
- TEMPORARY LIGHT FIXTURES SHALL BE THE SAME HEIGHT: 30" L-B62E (2DDW).
- JUMPERS SHALL BE RUN IN 1" HDPE CONDUIT WITH A SEPARATE #6 BARE COPPER GROUNO. SAND BAG CONDUIT 5' O.C., 5D LB MINIMUM PER SANO BAG.
- TEMPORARY THRESHOLD LIGHT BARS AND EDGE LIGHT ASSEMBLIES SHALL BE OFFERED TO THE STATE FOR SALVAGE AT COMPLETION OF THE PROJECT.
- B. TEMPORARY JUMPERS SHALL BE SALVAGED OR OISPOSED OF AT THE DIRECTION OF THE ENGINEER.



TEMPORARY THRESHOLD LIGHTING DETAIL - R/W 25 E6 SCALE: NTS







STATE OF ALASKA **DEPARTMENT OF TRANSPORTATION AND PUBLIC FACILITIES CENTRAL REGION**


KODIAK AIRPORT KODIAK, ALASKA
RUNWAY SAFETY AREA EXTENSION
PROJECT No. 53587
AIP No. 3-02-0158-017-2014 TEMPORARY LIGHTING DETAILS AND NOTES

3/18/2D14 SHEET E6 oF E19 AS-BUILT SHEET: a



FAA CONDUIT TRENCH DETAIL





2 R/W 36 REIL LAYOUT PLAN


R/W 25 REIL LAYOUT PLAN



BY DATE REVISION

STATE OF ALASKA
DEPARTMENT OF TRANSPORTATION
AND PUBLIC FACILITIES
CENTRAL REGION

KODIAK AIRPORT KODIAK, ALASKA RUNWAY SAFETY AREA EXTENSION PROJECT No. 53587 AIP No. 3-02-0158-017-2014 REIL DETAILS DATE: 3/18/2014 SHEET: E7 OF E19 AS-BUILT SHEET:



REIL WIRING DIAGRAM


THIS DRAWING IS FOR REFERENCE ONLY


|--|--|--|--|


STATE OF ALASKA
DEPARTMENT OF TRANSPORTATION
AND PUBLIC FACILITIES
CENTRAL REGION


KODIAK AIRPORT KODIAK, ALASKA RUNWAY SAFETY AREA EXTENSION PROJECT No. 53587 AIP No. 3-02-0158-017-2014 FAA REFERENCE DRAWING REIL WIRING DIAGRAM


DATE:
3/18/2D14
SHEET:
E8 OF E19
AS—BUILT SHEET:












1 VASI GROUNDING PLAN
E13 SCALE: NTS



2 TRENCH DETAIL
E13 SCALE NTS

OETAIL NOTE: COMPACT FILL IN 12" (MAX) LIFTS


THIS DRAWING IS FOR REFERENCE ONLY


BY	DATE	REVISION
		THE STATE OF THE S


STATE OF ALASKA
DEPARTMENT OF TRANSPORTATION
AND PUBLIC FACILITIES
CENTRAL REGION


KODIAK AIRPORT
KODIAK, ALASKA
RUNWAY SAFETY AREA EXTENSION
PROJECT No. 53587
AIP No. 3-02-0158-017-2014
FAA REFERENCE DRAWING
GROUNDING PLAN & TRENCH DETAIL


SHEET:
E13 OF E19
AS-BUILT SHEET:




















CONSTRUCTION SUMMARY:

WORK ASSOCIATED FOR THIS PHASE INCLUDES, BUT IS NOT LIMITED TO, THE FOLLOWING:

- . IMPLEMENT SAFETY PLAN REQUIREMENTS INCLUGEO IN THE SPCD.
- . IMPLEMENT BEST MANAGEMENT PRACTICES.
- . DEACTIVATE THE FAA GLIOE SLOPE AND REIL (TO BE PERFORMED BY FAA).
- . INSTALL TEMPORARY REIL
- INSTALL TEMPORARY THRESHOLD LIGHTS AS SHOWN OF THE PLANS.
- INSTALL TEMPORARY THRESHOLD BAR AND CHEVRONS AS SHOWN IN THE SAFETY PLAN DETAILS.

 COSTS THRESHOLD AND PLANTAY OF DESIGNATION AND PRESENT IN THE SAFETY PLAN DETAILS.

 COSTS THRESHOLD AND PLANTAY OF DESIGNATION AND PRESENT IN THE SAFETY PLAN.

 COSTS THRESHOLD BAR AND CHEVRONS AS SHOWN IN THE SAFETY PLAN.

 COSTS THRESHOLD BAR AND CHEVRONS AS SHOWN IN THE SAFETY PLAN.

 COSTS THRESHOLD BAR AND CHEVRONS AS SHOWN IN THE SAFETY PLAN.

 COSTS THRESHOLD BAR AND CHEVRONS AS SHOWN IN THE SAFETY PLAN.

 COSTS THRESHOLD BAR AND CHEVRONS AS SHOWN IN THE SAFETY PLAN.

 COSTS THRESHOLD BAR AND CHEVRONS AS SHOWN IN THE SAFETY PLAN.

 COSTS THRESHOLD BAR AND CHEVRONS AS SHOWN IN THE SAFETY PLAN.

 COSTS THRESHOLD BAR AND CHEVRONS AS SHOWN IN THE SAFETY PLAN.

 COSTS THRESHOLD BAR AND CHEVRONS AS SHOWN IN THE SAFETY PLAN.

 COSTS THRESHOLD BAR AND CHEVRONS AS SHOWN IN THE SAFETY PLAN.

 COSTS THRESHOLD BAR AND CHEVRONS AS SHOWN IN THE SAFETY PLAN.

 COSTS THRESHOLD BAR AND CHEVRONS AS SHOWN IN THE SAFETY PLAN.

 COSTS THRESHOLD BAR AND CHEVRONS AS SHOWN IN THE SAFETY PLAN.

 COSTS THRESHOLD BAR AND CHEVRONS AS SHOWN IN THE SAFETY PLAN.

 COSTS THRESHOLD BAR AND CHEVRONS AS SHOWN IN THE SAFETY PLAN.

 COSTS THRESHOLD BAR AND CHEVRONS AS SHOWN IN THE SAFETY PLAN.

 COSTS THRESHOLD BAR AND CHEVRONS AS SHOWN IN THE SAFETY PLAN.

 COSTS THRESHOWN IN THRESH
- COVER THRESHOLD AND RUNWAY 25 DESIGNATION NUMBER AS SHOWN IN THE SAFETY PLAN DETAILS.
- CONSTRUCT THE NEW EMBANKMENT FOR THE SAFETY AREA EXTENSION EAST OF THE EAST END
 OF RUNWAY 7/25 TO INCLUDE PLACING OF EMBANKMENT MATERIAL AND SHORE PROTECTION.
- REMOVE TEMPORARY LIGHTING AND MARKING FOLLOWING COMPLETION OF EMBANKMENTS.
- . RESTORE REIL SYSTEMS TO ITS ORIGINAL LOCATION (TO BE PERFORMED BY THE FAA).
- REACTIVATE GLIDESLOPE (TO BE PERFORMED BY THE FAA).

2. AREAS CLOSED TO AIRCRAFT OPERATIONS

THE THRESHOLD OF RUNWAY 25 WILL BE RELOCATED BY 500' TO THE WEST. THE FIRST 500' OF RUNWAY WILL BE CLOSED TO AIRCRAFT OPERATIONS.

3. TAXI ROUTES

TAXI ROUTES WILL NOT BE AFFECTED DURING THIS PHASE AND NO TAXIWAY WILL BE CLOSED.

4. ARFF ACCESS ROUTES

ARFF ACCESS ROUTES WILL NOT BE AFFECTED DURING THIS PHASE.

5. CONSTRUCTION HAUL ROUTES

ROUTES ARE SHOWN ON THE PHASING PLANS AND SHALL BE GENERALLY AS FOLLOWS:

THE PRIMARY HAUL ROUTE SHALL BE FROM REZANOF DRIVE WEST, EXIT ON DRIVEWAY LOCATED NORTH OF DEVIL'S CREEK. ENTER AGA THROUGH SECURITY GATE AND PROCEED EAST ALONG SERVICE ROAD SOUTH OF TAXIWAYS D AND C. CROSS RUNWAY 18/36 AND 11/29 TO THE SERVICE ROAD EAST OF RUNWAY 18/36. ENTER PROJECT AREA.

6.IMPACTS ON NAVAIDS

THE GLIDE SLOPE FOR RUNWAY 25 WILL BE DEACTIVATED DUE TO THE RELOCATION OF THE RUNWAY 25 THRESHOLD.

RUNWAY 25 VASI WILL BE DEACTIVATED AND TEMPORARILY RELOCATED 500' TO THE WEST. NEW TEMPORARY FOUNDATIONS WILL BE CONSTRUCTED AND TEMPORARY WIRING INSTALLED.

THE REIL WILL BE DEACTIVATED AND TEMPORARILY RELOCATED BY 500' TO THE WEST. NEW TEMPORARY WIRING AND LIGHT BASES WILL BE INSTALLED.

EXISTING VASI AND REIL EQUIPMENT WILL BE UTILIZED.

7.LIGHTING AND MARKING CHANGES

THE RUNWAY 25 THRESHOLD WILL BE RELOCATED BY APPROXIMATELY 500' TO THE WEST. THE RUNWAY EDGE LIGHTS AND THRESHOLD LIGHTS FOR THE CLOSEO END OF THE RUNWAY WILL BE DEACTIVATED. TEMPORARY THRESHOLD LIGHTS WILL BE INSTALLED AT THE RELOCATED THRESHOLD.

A TEMPORARY THRESHOLD BAR WILL BE PLACED AT THE NEW THRESHOLD WITH TEMPORARY CHEVRONS LEADING UP TO THE BAR.

THE RUNWAY THRESHOLD AND DESIGNATION NUMBERS WILL BE COVERED.

8. AVAILABLE RUNWAY LENGTH

RUNWAY LENGTH WILL BE SHORTENED TO 7,000' FEET DURING THIS PHASE. SEE THE DECLARED DISTANCES INCLUDED AS FOLLOWS:


RUNWAY 7

ASOA = 7,000' TORA = 7,000' TODA = 7,000' LDA = 7,000'

RUNWAY 25

ASOA = 6,000' TORA = 6,000' TODA = 6,000' LDA = 7,000'

THERE IS NO SAFETY AREA BEYOND THE ENDS OR PRIOR TO THE BEGINNING PF EACH RUNWAY.



1. CONSTRUCTION SUMMARY:

WORK ASSOCIATED FOR THIS PHASE INCLUDES, BUT IS NOT LIMITED TO, THE FOLLOWING:

- . IMPLEMENT SAFETY PLAN REQUIREMENTS INCLUDED IN THE SPCD.
- . IMPLEMENT BEST MANAGEMENT PRACTICES.
- . DEACTIVATE THE FAA GLIDE SLOPE, AND REIL (TO BE PERFORMED BY FAA).
- TEMPORARILY RELOCATE THE REIL LIGHTS AS SHOWN ON THE PLANS.
- INSTALL TEMPORARY THRESHOLD LIGHTS AS SHOWN OF THE PLANS.
 INSTALL TEMPORARY THRESHOLD BAR AND CHEVRONS AS SHOWN IN THE SAFETY PLAN DETAILS.
- . COVER RUNWAY 25 THRESHOLD AND DESIGNATION NUMBER AS SHOWN IN THE SAFETY PLAN DETAILS.
- . REGRADE THE SAFETY AREA, AS NEEDED.
- . SURFACE AND PAVE THE SAFETY AREA AS SHOWN ON THE PLANS.
- . INSTALL RUNWAY 7/25 EMAS.
- · MARK SAFETY AREA.
- · REMOVE TEMPORARY LIGHTING AND MARKING FOLLOWING COMPLETION OF EMBANKMENTS.
- . RESTORE THE REIL SYSTEMS TO THEIR ORIGINAL LOCATION.
- . REACTIVATE GLIDE SLOPE (TO BE PERFORMED BY THE FAA).

2. AREAS CLOSED TO AIRCRAFT OPERATIONS

THE THRESHOLD OF RUNWAY 25 WILL BE RELOCATED BY 500' TO THE WEST. THE FIRST 500' OF RUNWAY WILL BE CLOSED TO AIRCRAFT OPERATIONS.

3. TAXI ROUTES

TAXI ROUTES WILL NOT BE AFFECTED DURING THIS PHASE AND NO TAXIWAY WILL BE CLOSED.

4. ARFF ACCESS ROUTES

ARFF ACCESS ROUTES WILL NOT BE AFFECTED DURING THIS PHASE.

5. CONSTRUCTION ACCESS AND HAUL ROUTES

HAUL ROUTES ARE SHOWN ON THE PHASING PLAN AND SHALL BE GENERALLY AS FOLLOWS:

THE PRIMARY HAUL ROUTE FOR THE HAULING OF MATERIALS INCLUDING EMBANKMENT AND SHORE PROTECTION MATERIAL SHALL BE FROM REZANOF DRIVE WEST, EXIT ON DRIVEWAY LOCATED NORTH OF DEVIL'S CREEK. ENTER AOA THROUGH SECURITY GATE AND PROCEED EAST ALONG SERVICE ROAD SOUTH OF TAXIWAYS D AND C. CROSS RUNWAY 18/36 AND 11/29 TO THE SERVICE ROAD EAST OF RUNWAY 18/36. ENTER PROJECT AREA.

6.IMPACTS ON NAVAIDS

THE GLIDE SLOPE FOR RUNWAY 25 WILL BE DEACTIVATED DUE TO THE RELOCATION OF THE RUNWAY 25 THRESHOLD.

RUNWAY 25 VASI WILL BE DEACTIVATED AND TEMPORARILY RELOCATED 500' TO THE WEST. NEW TEMPORARY FOUNDATIONS WILL BE CONSTRUCTED AND TEMPORARY WIRING INSTALLED.

THE REIL WILL BE DEACTIVATED AND TEMPORARILY RELOCATED BY 500' TO THE WEST. NEW TEMPORARY WIRING AND LIGHT BASES WILL BE INSTALLED.

EXISTING VASI AND REIL EQUIPMENT WILL BE UTILIZED.

7. LIGHTING AND MARKING CHANGES

THE RUNWAY 25 THRESHOLD WILL BE RELOCATED BY APPROXIMATELY 500' TO THE WEST. THE RUNWAY EDGE LIGHTS AND THRESHOLD LIGHTS FOR THE CLOSED END OF THE RUNWAY WILL BE DEACTIVATED. TEMPORARY THRESHOLD LIGHTS WILL BE INSTALLED AT THE RELOCATED THRESHOLD.

A TEMPORARY THRESHOLD BAR WILL BE PLACED AT THE NEW THRESHOLD WITH TEMPORARY CHEVRONS LEADING UP TO THE BAR.

THE RUNWAY DESIGNATION NUMBER WILL BE COVERED.

8. AVAILABLE RUNWAY LENGTH

RUNWAY LENGTH WILL BE SHORTENED TO 7,033' FEET DURING THIS PHASE. SEE THE DECLARED DISTANCES INCLUDED AS FOLLOWS:


RUNWAY

ASDA = 7,000' TORA = 7,000' TODA = 7,000' LDA = 7,000'

RUNWAY 25

ASDA = 6,000' TORA = 6,000' TODA = 6,000' LDA = 7,000'

THERE IS NO SAFETY AREA BEYOND THE ENDS OR PRIOR TO THE BEGINNING OF EACH RUNWAY.



PHASE 2A NOTES:

1. CONSTRUCTION SUMMARY:

WORK ASSOCIATED WITH THIS PHASE INCLUDES, BUT IS NOT LIMITED TO, THE FOLLOWING:

- . IMPLEMENT SAFETY PLAN REQUIREMENTS INCLUDED IN THE SPCD.
- . IMPLEMENT BEST MANAGEMENT PRACTICES.
- DURING HOURS OF DAILY RUNWAY AND TAXIWAY CLOSURE:

- DEACTIVATE RUNWAY LIGHTS.
 DEACTIVATE VASI AND REIL FOR RUNWAY 36.
 PLACE ILLUMINATED HAZARD AREA BARRIERS AS SHOWN IN THE SAFETY PLAN DRAWINGS.
 CONSTRUCT THE NEW EMBANKMENT AND SHORE AT THE SOUTH END OF RUNWAY 18—36.
- . FOLLOWING THE HOURS OF DAILY RUNWAY AND TAXIWAY CLOSURE:

 - REMOVE FOD FROM RUNWAY AND TAXWAY SURFACES.
 FOLLOWING THE CLOSURE, REMOVE THE BARRIERS, "X"S.
 RESTORE RUNWAY LIGHTING, VASI AND REIL SYSTEMS.

2. AREAS CLOSED TO AIRCRAFT OPERATIONS

RUNWAY 18-36 TAXIWAY A AND TAXIWAY B NAY BE CLOSED FROM 6:30 P.M. TO 6:30 A.M. DURING THIS PHASE.

3. DURATION OF CLOSURES

THIS PHASE IS EXPECTED TO BEGIN IN JUNE, 2014 AND BE COMPLETED BY DECEMBER, 2014.

4. TAXI ROUTES

TAXIWAY A AND B WILL BE CLOSED DURING PERIODS OF RUNWAY CLOSURE.

5. ARFF ACCESS ROUTES

ARFF ACCESS ROUTES WILL NOT BE AFFECTED DURING THIS PHASE.

6. HAUL ROUTES

THE HAUL ROUTES SHALL BE FROM REZANOF DRIVE WEST, EXIT ON DRIVEWAY LOCATED NORTH OF DEVILS CREEK, ENTER AGA THROUGH SECURITY GATE AND PROCEED ALONG THE SERVICE ROAD SOUTH OF TAXIWAYS D AND C, AND SOUTH ALONG THE WEST SIDE OF TAXIWAY B. CROSS TAXIWAY A AND ENTER PROJECT AREA.

7. IMPACTS ON NAVAIDS


THE RUNWAY 36 VASI AND REIL WILL BE DEACTIVATED DURING HOURS OF RUNWAY CLOSURE BY EITHER OBSCURING THE LIGHTS OR TURNING OFF POWER. (AS DIRECTED BY FAA)

8. LIGHTING AND MARKING CHANGES

THE RUNWAY LIGHTS WILL BE DEACTIVATED DURING HOURS OF RUNWAY CLOSURE.

9. AVAILABLE RUNWAY LENGTH

THE LENGTH OF RUNWAY 18-36 WILL BE TO 5,009°.





=			STATE OF ALASKA
			DEPARTMENT OF TRANSPORTATION AND PUBLIC FACILITIES
BY	DATE	REVISION	CENTRAL REGION

KODIAK AIRPORT
KODIAK, ALASKA
KODIAK AIRPORT RSA EXTENSION, 2014
PROJECT No. 53587 AIP No. 3-02-0158-017-2014 PHASING PLAN PHASE 2A

3/18/2014 AD4 of 15 AS-BUILT SHEET: ar

PHASE 2B NOTES: 1. CONSTRUCTION SUMMARY:

WORK ASSOCIATED WITH THIS PHASE INCLUDES, BUT IS NOT LIMITED TO, THE FOLLOWING:

- . IMPLEMENT SAFETY PLAN REQUIREMENTS INCLUDED IN THE SPCD.
- . IMPLEMENT BEST MANAGEMENT PRACTICES.
- . DURING HOURS OF DAILY RUNWAY AND TAXIWAY CLOSURE:
 - DEACTIVATE RUNWAY LIGHTS.
 - DEACTIVATE VASI AND REIL FOR RUNWAY 36.
- PLACE LIGHTED "X"S OVER RUNWAY RESIGNATION MARKERS FOR RUNWAY 18 AND 36.
 PLACE ILLUMINATED HAZARD AREA BARRIERS AS SHOWN IN THE SAFETY PLAN DRAWINGS,
- CONSTRUCTION DURING THIS PHASE WILL INCLUDE
- COMPLETE CONSTRUCTION OF THE SOUTHERN EMBANKMENT EXTENSION. CONSTRUCT SOUTHERN EXTENSION OF RUNWAY, TAXIWAY A.
- CONSTRUCT SAFETY AREA.
- PAVE BLAST PAD. CONSTRUCT SERVICE ROAD.
- INSTALL LIGHTING.
- FOLLOWING THE HOURS OF DAILY RUNWAY AND TAXIWAY CLOSURE:

 REMOVE FOD FROM RUNWAY AND TAXIWAY SURFACES.

 FOLLOWING THE CLOSURE, REMOVE THE BARRIERS, "X"S.

 RESTORE RUNWAY LIGHTING, VASI AND REIL SYSTEMS.
- 2. AREAS CLOSED TO AIRCRAFT OPERATIONS

RUNWAY 18-36, TAXIWAY A AND B MAY BE CLOSED FROM 6:30 P.M. TO 6:30 A.M. DURING THIS PHASE.

3. DURATION OF CLOSURES

THIS PHASE IS EXPECTED TO BEGIN IN JUNE, 2014 AND BE COMPLETED BY DECEMBER, 2014.

4. TAXI ROUTES

TAXIWAY A AND B WILL BE CLOSED DURING PERIODS OF RUNWAY CLOSURE.

5. ARFF ACCESS ROUTES

ARFF ACCESS ROUTES WILL NOT BE AFFECTED DURING THIS PHASE.

6. HAUL ROUTES

THE HAUL ROUTES SHALL BE FROM REZANOF DRIVE WEST, EXIT ON DRIVEWAY LOCATED NORTH OF DEVILS CREEK, ENTER AOA THROUGH SECURITY GATE AND PROCEED EAST ALONG THE SERVICE ROAD SOUTH OF TAXIWAYS D AND C, AND SOUTH ALONG THE WEST SIDE OF TAXIWAY B. CROSS TAXIWAY A AND ENTER PROJECT


THE RUNWAY 36 VASI AND REIL WILL BE DEACTIVATED DURING HOURS OF RUNWAY CLOSURE BY EITHER OBSCURING THE LIGHTS OR TURNING OFF POWER. (AS DIRECTED BY FAA)

8. LIGHTING AND MARKING CHANGES

THE RUNWAY LIGHTS WILL BE DEACTIVATED DURING HOURS OF RUNWAY CLOSURE.

9. AVAILABLE RUNWAY LENGTH

THE LENGTH OF RUNWAY 18-36 WILL BE TO 5,009'.






STATE OF ALASKA **DEPARTMENT OF TRANSPORTATION** AND PUBLIC FACILITIES **CENTRAL REGION** PREPARED BY: HDR Alaska, Inc. BY DATE REVISION

KODIAK AIRPORT KODIAK, ALASKA KODIAK AIRPORT RSA EXTENSION, 2014 PROJECT No. 53587 AIP No. 3-02-0158-017-2014 PHASING PLAN PHASE 2B

3/18/2014 AD5 of 15 AS-BUILT SHEET: OF



1. CONSTRUCTION SUMMARY:

WORK ASSOCIATED WITH THIS PHASE INCLUDES, BUT IS NOT LIMITED TO, THE FOLLOWING:

- · IMPLEMENT SAFETY PLAN REQUIREMENTS INCLUDED IN THE SPCD.
- PLACE LIGHTED RUNWAY CLOSURE MARKERS AT ENDS OF RUNWAY AS SHOWN IN THE SAFETY PLAN.
- . DEACTIVATE RUNWAY AND TAXIWAY LIGHTS FOR THE PROJECT AREA.
- · PLACE HAZARD BARRIERS AS SHOWN IN THE SAFETY PLAN.
- . REMOVE THRESHOLD EDGE LIGHTS, AS REQUIRED, FOR RUNWAY 18.
- INSTALL NEW THRESHOLD LIGHTS FOR THE RELOCATED THRESHOLD OF RUNWAY 18.
 REMOVE EXISTING RUNWAY AND TAXIWAY STRIPING AS SHOWN ON THE MARKING
- DEMOLITION PLAN.
 INSTALL EMAS AT NORTH END OF THE RUNWAY 18/36 SAFETY AREA.
- · MARK RUNWAY 18/36, TAXIWAY A AND TAXIWAY B AS SHOWN ON THE PLANS.
- · REFURBISH VASI
- REPAVE TAXIWAY C
- . INSTALL NEW SEGMENTED CIRCLE AND LIGHTED WIND CONE
- REMOVE EXISTING SEGMENTED CIRCLE AND LIGHTED WIND CONE
- . INSTALL REILS AT THEIR NEW LOCATIONS.
- REACTIVATE RUNWAY, TAXIWAY LIGHTS AND NAVAIDS.
 REMOVE CLOSURE MARKERS AND BARRIERS.
- 2. AREAS CLOSED TO AIRCRAFT OPERATIONS

RUNWAY 18/36 SHALL BE CLOSED TO AIRCRAFT OPERATIONS.

TAXIWAYS A AND C BETWEEN TAXIWAY B AND RUNWAY 18/36 SHALL BE CLOSED.

3. DURATION OF CLOSURES

PHASE 2C WILL BEGIN IMMEDIATELY FOLLOWING COMPLETION OF PHASE 2B (APPROXIMATELY AUGUST, 2015) AND SHALL BE COMPLETED BY NOVEMBER 30, 2015.

4. TAXI ROUTES

AIRCRAFT WILL USE TAXIWAY A AND B TO ACCESS RUNWAYS 7/25 AND 11/29.

5. ARFF ACCESS ROUTES

ARFF ACCESS ROUTES WILL NOT BE AFFECTED DURING THIS PHASE.

6. CONSTRUCTION ACCESS AND HAUL ROUTES

ACCESS TO THE HAUL ROUTES IS SHOWN ON THE PHASING PLAN AND SHALL BE GENERALLY AS FOLLOWS:

THE ACCESS ROUTE WILL BE FROM REZANOF DRIVE WEST, PROCEED VIA 8TH STREET AND G AVENUE TO THE SECURITY GATE ADJACENT TO THE USCG ARFF FACILITY. ENTER THE AOA AND PROCEED EAST ALONG SERVICE ROAD SOUTH OF TAXIWAYS D AND C AND WEST OF TAXIWAY B. CROSS TAXIWAY A AND ENTER PROJECT AREA.

ALTERNATE ACCESS WILL BE FROM REZANOF DRIVE WEST, PROCEED FROM THE TERMINAL ENTRANCE ROAD TO THE DEVIL'S CREEK SERVICE ROAD. ENTER THE AOA THROUGH THE GATE AT DEVIL'S CREEK AND THEN PROCEED VIA THE EXISTING SERVICE ROADS NORTH ALONG TAXIWAY E AND EAST ON THE NORTH SIDE OF RUNWAYS 11/29 AND 7/25 TO THE PROJECT AREA.

7. IMPACTS ON NAVAIDS


THE RUNWAY 36 VASI AND REIL LIGHTS WILL BE DEACTIVATED. VASI WILL BE REFURBISHED AND REIL LIGHTS RELOCATED TO THEIR FINAL POSITION.


8. LIGHTING AND MARKING CHANGES

TEMPORARY LIGHTED RUNWAY CLOSURE MARKERS SHALL BE PLACED ON RUNWAY CENTERLINE ON OR NEAR THE EXISTING OR RELOCATED RUNWAY DESIGNATION NUMBERS DEPENDING ON CONSTRUCTION AND MARKING ACTIVITIES.

9. AVAILABLE RUNWAY LENGTH

RUNWAY 18/36 SHALL BE CLOSED.







			STATE OF ALASKA
			DEPARTMENT OF TRANSPORTATION
		and the second s	AND PUBLIC FACILITIES
BY	DATE	REVISION	CENTRAL REGION

KODIAK AIRPORT
KODIAK, ALASKA
KODIAK ARPORT RSA EXTENSION, 2014
PROJECT No. 53587
AIP No. 3-02-0158-017-2014
PHASING PLAN

SHEET: AD6 of 15 AS-BUILT SHEET:


GENERAL SAFETY PLAN NOTES:


- 1. SUBMIT A SAFETY PLAN COMPLIANCE DOCUMENT (SPCD) PER FAA AC 150/5370-2F, OPERATIONAL SAFETY ON AIRPORTS DURING CONSTRUCTION (SAFETY AC), WITHIN 30 DAYS OF RECEIVING NOTICE TO PROCEED (NTP) TO THE ENGINEER FOR APPROVAL.
- FOLLOWING APPROVAL OF THE SPCD, IF SUBSEQUENT CHANGES ARE NEEDED, SUBMIT A REVISION TO THE ENGINEER FOR REVIEW AND APPROVAL. ALLOW UP TO 40 DAYS FOR REVIEW OF REVISED SPCD.
- SEE SHEETS AD9 THROUGH AD15 FOR CONSTRUCTION PHASE SPECIFIC SAFETY PLANS.
- WHENEVER THE PLANS OR SPECIFICATIONS CALL FOR COORDINATION, NOTIFICATION, CONTACT, OR OTHER INTERACTION WITH FAA, AIRPORT MANAGEMENT, MAINTENANCE AND OPERATIONS, ARFF PERSONNEL, AIRPORT TENANTS, AIRPORT USERS, ANY LOCAL, STATE, OR FEDERAL AGENCY, GROUP, OR ASSOCIATION, OR THE GENERAL PUBLIC, SUCH ACTIVITY SHALL BE DONE THROUGH, IN THE PRESENCE OF, OR WITH THE WRITTEN APPROVAL OF THE ENGINEER. ALLOW SUFFICIENT TIME FOR COORDINATION AND APPROVALS WITHIN PROPOSED WORK SCHEDULES. SEE THE CSPP FOR REQUIRED LEAD TIMES FOR COORDINATION WITH CERTAIN GROUPS.
- THE CONTRACTOR MUST REPORT ANY SAFETY ISSUES TO THE ENGINEER AND AIRPORT MANAGER UPON DISCOVERY. THE CONTRACTOR MUST TAKE IMMEDIATE ACTION TO RESOLVE SAFETY ISSUES AS DIRECTED.
- THE TERM "ACTIVE RUNWAY" REFERS TO RUNWAY OR PORTION OF THE RUNWAY OPEN TO LANDING, TAKEOFF AND TAXING OPERATIONS.
- NO CONSTRUCTION ACTIVITY IS ALLOWED WITHIN THE RUNWAY SAFETY AREA (RSA) OF THE ACTIVE RUNWAY. NO CONSTRUCTION ACTIVITY IS ALLOWED WITHIN THE TAXIWAY SAFETY AREA (TSA) OR TAXIWAY OBJECT FREE AREA (TOFA) WHILE THE TAXIWAY IS OPEN FOR AIRCRAFT OPERATIONS. COORDINATE ANY RESTRICTIONS TO AIRCRAFT OPERATIONS WITH AIRPORT USERS AND THE AIRPORT
- DO NOT STORE MATERIALS OR PARK EQUIPMENT WITHIN THE OFA OF THE ACTIVE RUNWAY. USE STOCKPILE AND STAGING AREAS SHOWN TO STORE MATERIALS OR PARK EQUIPMENT. EQUIPMENT MAY BE PARKED IN THE "CONSTRUCTION AREA" PROVIDED IT DOES NOT CONFLICT WITH OTHER LIMITATIONS. ALL TEMPORARY STAGING AND STOCKPILE LOCATIONS OTHER THAN "STOCKPILE AREA" REQUIRE

- APPROVAL OF THE ENGINEER. ENSURE ADEQUATE DISTANCE FOR JET AND PROP BLAST PROTECTION.
- 9. EQUIPMENT WILL NOT BE ALLOWED OUTSIDE OF THE FOOTPRINT OF THE PROJECT EXCEPT FOR EXISTING PADS AS APPROVED BY THE
- 10. EQUIPMENT WILL ONLY BE PERMITTED INSIDE THE AIRPORT OPERATIONS AREAS (AOA) AS APPROVED BY THE AIRPORT MANAGER THROUGH THE ENGINEER. SEE GCP-80 OF THE SPECIFICATIONS FOR LIMITATIONS AND OPERATIONAL SAFETY CONCERNS.
- 11. SNOW OR EARTH BERMS, STORAGE OF EQUIPMENT AND MATERIALS OR ANY GROUND DISTURBING ACTIVITIES WILL NOT BE ALLOWED IN THE GLIDESLOPE CRITICAL AREA EXCEPT FOR WORK DEPICTED ON THE PLANS WHILE THE GLIDESLOPE IS SHUT DOWN AND BEFORE FAA CONDUCTS THE FLIGHT CHECK.
- 12. ARFF MUST HAVE ACCESS TO THE ENTIRE AIRPORT DURING EMERGENCIES. MAINTAIN SUITABLE CORRIDORS AND COORDINATE ACCESS WITH ARFF PERSONNEL THROUGH THE ENGINEER AS
- 13. MAINTAIN AIRCRAFT ACCESS TO TAXIWAYS AND APRONS DURING AIR OPERATIONS AS SHOWN ON THE PLANS. WHEN TAXIWAYS ARE CLOSED, HAZARD BARRIERS NEED TO BE PLACED AS SHOWN ON THE PLANS. CONTACT THE AIRPORT MANAGER AND AFFECTED PARTIES 45 DAYS PRIOR TO FULL CLOSURE OF ANY TAXIWAY (SEE CSPP FOR MORE INFORMATION).
- 14. RUNWAY AND TAXIWAY WORK AREA LIMITS WILL BE TEMPORARILY CLOSED FOR AIRCRAFT OPERATIONS AS SHOWN ON THE SAFETY AND PHASING PLAN SHEETS AND IN ACCORDANCE WITH CSPP AND THE APPROVED SPCD.
- 15. MARK OPEN TRENCHES OR EXCAVATIONS WITH HAZARD AREA BARRIERS. LIGHT WITH RED LIGHTS DURING HOURS OF RESTRICTED VISIBILITY OR DARKNESS. SEE CSPP (SECTION 18) REGARDING RESTRICTIONS FOR TRENCH AND EXCAVATION LOCATIONS
- 16. HAZARDOUS AREA BARRIERS MAY BE REQUIRED AT ADDITIONAL LOCATIONS, OR ADJUSTMENT MAY BE REQUIRED. LOCATE BARRIERS AS DIRECTED BY THE ENGINEER. SEE HAZARDOUS AREA BARRIER DETAIL ON SAFETY PLAN DETAILS SHEET.
- 17. COORDINATE THROUGH THE ENGINEER FOR CONTRACTOR ACTIVITIES

- THAT MAY INTERFERE WITH THE OFA AND WEATHER INSTRUMENTS. SEE THIS SHEET FOR VERTICAL CLEARANCES.
- 18. MONITOR TEMPORARY MARKINGS AND LIGHTING SYSTEMS FREQUENTLY AND TAKE ACTION TO CORRECT DEFICIENCIES IMMEDIATELY UPON DISCOVERY AND NOTIFICATION.
- 19. CARRY OUT CONTINUING COORDINATION THROUGH THE ENGINEER USING WEEKLY EMAIL UPDATES AND PROGRESS MEETINGS WITH THE AIRPORT MANAGER, AIRPORT MAINTENANCE, ARFF PERSONNEL AIRPORT USERS AND OTHER PARTIES LISTED IN SECTION 1A OF THE
- 20. PROVIDE WATER FOR DUST CONTROL AS REQUIRED, AND AS DIRECTED. DUST, SMOKE, STEAM, OR OTHER AIRBORNE PARTICULATES CAUSED BY CONTRACTOR ACTIVITIES MAY BE CONSIDERED A SAFETY VIOLATION.
- 21. KEEP ALL ACTIVE HAUL ROUTES AND AIRPORT SURFACES CLEAN OF MATERIAL. REMOVE SPILLED OR TRACKED MATERIAL IMMEDIATELY TO AVOID VEHICLE ACCIDENTS OR AIRCRAFT DAMAGE.
- 22. REMOVE ALL FOREIGN OBJECT DEBRIS (FOD) IMMEDIATELY UPON DISCOVERY OR NOTIFICATION. FAILURE TO REMOVE FOD MAY BE CONSIDERED A SAFETY VIOLATION AS DETERMINED BY THE ENGINEER.
- 23. WHEN A RUNWAY IS OPEN TO AIRCRAFT OPERATIONS. CONSTRUCTION, INCLUDING EXCAVATIONS, MAY BE PERMITTED IN THE ROFA. HOWEVER, EQUIPMENT MUST BE REMOVED FROM THE ROFA WHEN NOT IN USE, AND MATERIAL SHOULD NOT BE STOCKPILED IN THE ROFA IF NOT NECESSARY, STOCKPILING MATERIAL IN THE OFA REQUIRES SUBMITTAL OF A 7460-1 FORM AND JUSTIFICATION PROVIDED TO THE APPROPRIATE FAA AIRPORTS REGIONAL OR DISTRICT OFFICE FOR APPROVAL. NO EQUIPMENT OR VEHICLES ARE TO BE PARKED, OR LEFT UNATTENDED, IN THE ROFA AT ANY TIME.
- 24. KEEP ALL WORKERS, EQUIPMENT AND MATERIALS OUTSIDE OF THE ACTIVE RUNWAY SAFETY AREA, NAVAID CRITICAL AREAS, AND APPROACH SURFACES DURING AIRCRAFT OPERATIONS, AND ONLY ENTER THESE AREAS AS REQUIRED AND AS APPROVED.
- 25. KEEP ALL WORKERS, EQUIPMENT, AND MATERIALS OUTSIDE OF THE TAXIWAY SAFETY AREAS AND TAXIWAY OBJECT FREE AREAS WHILE TAXIWAYS ARE OPEN TO AIRCRAFT. ALL TAXING AIRCRAFT HAVE THE

- 26. PROVIDE AN AIRPORT FLAGGER IF HAULING ACROSS AN ACTIVE TAXIWAY AND/OR ACTIVE RUNWAY AND IS APPROVED AND INCLUDED IN THE APPROVED SPCD.
- 27. PROVIDE A GATE GUARD IF ANY GATE REMAINS OPEN DURING CONSTRUCTION ACTIVITIES.
- 28. TEMPORARY CLOSURE OF ANY RUNWAY OR TAXIWAY MUST BE DEPICTED IN THE APPROVED SPCD. COORDINATE WITH THE AIRPORT MANAGER, FAA, AIRPORT TENANTS AND OPERATORS, THROUGH THE ENGINEER AT LEAST 45 DAYS IN ADVANCE OF ACTUAL CLOSURES. REFER TO THE SCPP FOR ALLOWED CLOSURE DURATIONS.
- 29. HAZARDOUS AREA BARRIERS FOR THE CONTRACTOR'S USE ARE AVAILABLE FROM THE AIRPORT MANAGER. FLAGS AND FLASHERS MAY ALSO BE AVAILABLE. THE CONTRACTOR SHALL CONFIRM AVAILABILITY AND PROVIDE ADDITIONAL FLAGS AND FLASHERS AS REQUIRED. THE CONTRACTOR SHALL ALSO PROVIDE FRESH BATTERIES FOR FLASHERS.
- 30. PROVIDE PICK UP BROOM TRUCK (STREET SWEEPER), OR OTHER EQUIPMENT AS APPROVED FOR CONTROL OF FOD ON ACTIVE SURFACES. CLEAN ACTIVE SURFACES OF FOD IMMEDIATELY UPON DISCOVERY OR NOTIFICATION





APPROACH / DEPARTURE SURFACES (TYPICAL) NTS

PHASE 1A AND 1B	RSA OR TSA (ft.)*	OFZ (ft.)*	OFA (ft.)*	PRIMARY SURFACE (ft.)*
RW 7-25	150	200	400	500
PHASE 1A AND 1B	RSA OR TSA (ft.)*	OFZ (ft.)*	OFA (ft.)*	PRIMARY SURFACE (ft.)*
RW 18-36	150	200	400	500
TW A	85.5			N/A
TW B	85.5			N/A


* DISTANCE MEASURED FROM RW OR TW CENTERLINE

STATE OF ALASKA **DEPARTMENT OF TRANSPORTATION AND PUBLIC FACILITIES CENTRAL REGION** PREPARED BY: HDR Alaska, Inc. BY DATE REVISION

KODIAK AIRPORT KODIAK, ALASKA KODIAK AIRPORT RSA EXTENSION, 2014 PROJECT No. 53587 AIP No. 3-02-0158-017-2014


SAFETY PLAN NOTES

3/18/2014 AD7 of 15 AS-BUILT SHEET: OF



PHASE 1A SAFETY PLAN NOTES:

- KEEP ALL PERSONS, EQUIPMENT, AND TEMPORARY STOCKPILES CLEAR OF THE 20:1 APPROACH / DEPARTURE SURFACE OF THE RUNWAY 25 RELOCATED THRESHOLD DURING AIRCRAFT OPERATIONS ON RUNWAY 7/25. THIS INCLUDES STAYING CLEAR OF THE APPROACH / DEPARTURE SURFACES 15 MINUTES PRIOR TO LANDING AND 15 MINUTES AFTER DEPARTURE. NOTE THE 20:1 SURFACE BEGINS 200 FEET PRIOR TO (EAST) THE RELOCATED THRESHOLD AND HAS THE ELEVATION OF THE CENTERLINE OF THE RELOCATED THRESHOLD.
- THE ELEVATION OF THE 20:1 SURFACE REMAINS THE SAME REGARDLESS OF THE OFFSET FROM THE
 CENTERLINE, BUT THE HEIGHT ABOVE THE GROUND VARIES WITH THE TERRAIN AS THE OFFSET AND
 GROUND ELEVATION CHANGES. THE SURFACE ITSELF IS IMAGINARY, AND IS REQUIRED TO BE FREE OF
 OBSTRUCTIONS TO SUPPORT THE APPROVED APPROACH PROCEDURE FOR RUNWAY 7/25.
- USE THE DESIGNATED HAUL ROUTES FOR THIS PHASE AS SHOWN ON SAFETY PLAN OVERVIEW SHEET.
 ALTERNATE HAUL ROUTES MUST BE APPROVED AND DEPICTED IN THE APPROVED SPCD.
- GLIDE SLOPE WILL BE DEACTIVATED DURING PHASE 1A. THERE WILL BE NO RESTRICTIONS WITHIN THE GLIDESLOPE CRITICAL AREA AFTER DEACTIVATION.



CONSTRUCTION AREA

CONTRACTOR STAGING AREA

HAZARD AREA BARRIERS

HAUL ROUTE

FLAGGER

PHASE 1B SAFETY PLAN NOTES: 1. KEEP ALL PERSONS, EQUIPMENT, AND TEMPORARY STOCKPILES CLEAR OF THE 20:1 APPROACH / DEPARTURE SURFACE OF THE RUNWAY 25 RELOCATED THRESHOLD DURING AIRCRAFT OPERATIONS ON RUNWAY 7/25. THIS INCLUDES STAYING CLEAR OF THE APPROACH / DEPARTURE SURFACES 15 MINUTES PRIOR TO LANDING AND 15 MINUTES AFTER DEPARTURE. NOTE THE 20:1 SURFACE BEGINS 200 FEET PRIOR TO (EAST) THE RELOCATED THRESHOLD AND HAS THE ELEVATION OF THE CENTERLINE OF THE RELOCATED THRESHOLD. 2. THE ELEVATION OF THE 20:1 SURFACE REMAINS THE SAME REGARDLESS OF THE OFFSET FROM THE CENTERLINE, BUT THE HEIGHT ABOVE THE GROUND VARIES WITH THE TERRAIN AS THE OFFSET AND GROUND ELEVATION CHANGES. THE SURFACE ITSELF IS IMAGINARY, AND IS REQUIRED TO BE FREE OF OBSTRUCTIONS TO SUPPORT THE APPROVED APPROACH PROCEDURE FOR RUNWAY 7/25. EDGE BUSKIN RIVER 3. USE THE DESIGNATED HAUL ROUTES FOR THIS PHASE AS SHOWN. ALTERNATE HAUL ROUTES MUST BE APPROVED AND DEPICTED IN THE APPROVED SPCD. 4. GLIDESLOPE WILL BE DEACTIVATED DURING PHASE 1B. THERE WILL BE NO RESTRICTIONS WITHIN THE 0 GLIDESLOPE CRITICAL AREA AFTER DEACTIVATION. STA 175+33.48 RUNWAY 25 THRESHOLD STA 170+00 RUNWAY 25 TEMPORARY THRESHOLD RW 7/25 S87'59'18.41"E VASI 8 OFZ GLIDESLOPE GLIDESLOPE CRITICAL AREA TEMPORARY MARKING AND LIGHTING SEE SAFETY PLAN SHEETS AD14 AND AD15 FOR DETAILS LEGEND CONSTRUCTION AREA CONTRACTOR STAGING AREA HAZARD AREA BARRIERS HAUL ROUTE SECURITY GATE WITH FLAGGER KODIAK AIRPORT KODIAK, ALASKA KODIAK AIRPORT RSA EXTENSION, 2014 PROJECT No. 53587 AIP No. 3-02-0158-017-2014 STATE OF ALASKA 3/26/2014 **DEPARTMENT OF TRANSPORTATION** AD100F 15

PREPARED BY: HDR Alaska, Inc. BY DATE

REVISION

AND PUBLIC FACILITIES

CENTRAL REGION

AS-BUILT SHEET:


OF

SAFETY PLAN PHASE 1B

PREPARED BY: HDR Alaska, Inc. BY DATE

REVISION


- 1. KEEP ALL PERSONS, EQUIPMENT, AND TEMPORARY STOCKPILES CLEAR OF THE 20:1 APPROACH / DEPARTURE SURFACE OF THE RUNWAY 36 THRESHOLD DURING AIRCRAFT OPERATIONS ON RUNWAY 18/36. THIS INCLUDES STAYING CLEAR OF THE APPROACH / DEPARTURE SURFACES 15 MINUTES PRIOR TO LANDING AND 15 MINUTES AFTER DEPARTURE. NOTE THE 20:1 SURFACE BEGINS 200 FEET PRIOR TO (SOUTH OF) THE THRESHOLD AND HAS THE ELEVATION OF THE CENTERLINE OF THE THRESHOLD.
- 2. THE ELEVATION OF THE 20:1 SURFACE REMAINS THE SAME REGARDLESS OF THE OFFSET FROM THE CENTERLINE, BUT THE HEIGHT ABOVE THE GROUND VARIES WITH THE TERRAIN AS THE OFFSET AND GROUND ELEVATION CHANGES. THE SURFACE ITSELF IS IMAGINARY, AND IS REQUIRED TO BE FREE OF OBSTRUCTIONS TO SUPPORT THE APPROVED APPROACH PROCEDURE FOR RUNWAY 18/36.
- 3. USE THE DESIGNATED HAUL ROUTES FOR THIS PHASE AS SHOWN. ALTERNATE HAUL ROUTES MUST BE APPROVED AND DEPICTED IN THE APPROVED SPCD.
- 4. TAXIWAY A AND B CLOSURE AND MOVEMENT OF AIRCRAFT:
 - . THE CONTRACTOR SHALL KEEP TAXIWAY A AND B OPEN AND USEABLE FOR THE PASSAGE OF AIRCRAFT AT ALL TIMES WITH THE FOLLOWING RESTRICTIONS:
 - . TAXIMAY A WILL REMAIN OPENED FOR THE PASSAGE OF AIRCRAFT, UNDER POWER, FROM 6:30 A.M. TO 6:30 P.M. THE CONTRACTOR MAY CONTINUE TO WORK ON THE TAXIWAY DURING THIS TIME PERIOD, PROVIDED THAT HE NOT DELAY PASSAGE OF AIRCRAFT BY MORE THAN 30 MINUTES FROM NOTIFICATION BY ENGINEER, AIRPORT MANAGER, THE ATCT OR AIR STATION KODIAK OPERATIONS CENTER OF THE ARRIVAL OR DEPARTURE
 - . TAXIWAY A MAY BE CLOSED FROM 6:30 P.M. TO 6:30 A.M. WITH THE RESTRICTION THAT IT MUST BE AVAILABLE FOR MOVEMENT OF AIRCRAFT, UNDER TOW, FOR CRITICAL OPERATIONS AS STATED BELOW.
 - · IN THE EVENT OF A CRITICAL OPERATION SUCH AS SEARCH AND RESCUE, DISASTER RELIEF, AIRCRAFT MECHANICAL PROBLEM FOR A MISSION CRITICAL AIRCRAFT, OR OTHER EMERGENCY, REGARDLESS OF THE TIME, THE CONTRACTOR SHALL IMMEDIATELY PROVIDE FOR PASSAGE OF ANY AIRCRAFT, WITH A MAXIMUM 15 MINUTE DELAY FROM TIME OF NOTIFICATION BY THE ENGINEER, AIRPORT MANAGER, ATCT OR OPERATIONS CENTER.
- 5. RUNWAY 18-36 TEMPORARY CLOSURE:
 - . RUNWAY 18-36 MAY BE CLOSED FROM 6:30 P.M. TO 6:30 A.M. DURING THIS PHASE.
 - . PLACE ILLUMINATED RUNNING CLOSURE MARKERS OVER RUNWAY DESIGNATION NUMBERS OF EACH RUNWAY.
 - · PLACE HAZARDOUS BARRIERS WITH FLAGS AND FLASHERS AS INDICATED ON PLANS.




CONTRACTOR STAGING AREA

OF

- 1. KEEP ALL PERSONS, EQUIPMENT, AND TEMPORARY STOCKPILES CLEAR OF THE 20:1 APPROACH / DEPARTURE SURFACE OF THE RUNWAY 38 THRESHOLD DURING AIRCRAFT OPERATIONS ON RUNWAY 18/36. THIS INCLUDES STAYING CLEAR OF THE APPROACH / DEPARTURE SURFACES 15 MINUTES PRIOR TO LANDING AND 15 MINUTES AFTER DEPARTURE. NOTE THE 20:1 SURFACE BEGINS 200 FEET PRIOR TO (SOUTH OF) THE THRESHOLD AND HAS THE ELEVATION OF THE CENTERLINE OF THE THRESHOLD.
- 2. THE ELEVATION OF THE 20:1 SURFACE REMAINS THE SAME REGARDLESS OF THE OFFSET FROM THE CENTERLINE, BUT THE HEIGHT ABOVE THE GROUND VARIES WITH THE TERRAIN AS THE OFFSET AND GROUND ELEVATION CHANGES. THE SURFACE ITSELF IS IMAGINARY, AND IS REQUIRED TO BE FREE OF OBSTRUCTIONS TO SUPPORT THE APPROVED APPROACH PROCEDURE FOR RUNWAY 18/36.
- 3. USE THE DESIGNATED HAUL ROUTES FOR THIS PHASE AS SHOWN. ALTERNATE HAUL ROUTES MUST BE APPROVED AND DEPICTED IN THE APPROVED SPCD.
- 4. TAXIWAY A AND B CLOSURE AND MOVEMENT OF AIRCRAFT:
 - . THE CONTRACTOR SHALL KEEP TAXIWAY A AND B OPEN AND USEABLE FOR THE PASSAGE OF AIRCRAFT AT ALL TIMES WITH THE FOLLOWING RESTRICTIONS:
 - TAXIWAY A WILL REMAIN OPENED FOR THE PASSAGE OF AIRCRAFT, UNDER POWER, FROM 6:30 A.M. TO 6:30 P.M. THE CONTRACTOR MAY CONTINUE TO WORK ON THE TAXIWAY DURING THIS TIME PERIOD, PROVIDED THAT HE NOT DELAY PASSAGE OF AIRCRAFT BY MORE THAN 30 MINUTES FROM NOTIFICATION BY ENGINEER, AIRPORT MANAGER, THE ATCT OR AIR STATION KODIAK OPERATIONS CENTER OF THE ARRIVAL OR DEPARTURE
 - TAXIWAY A MAY BE CLOSED FROM 6:30 P.M. TO 6:30 A.M. WITH THE RESTRICTION THAT IT MUST BE AVAILABLE FOR MOVEMENT OF AIRCRAFT, UNDER TOW, FOR CRITICAL OPERATIONS AS STATED BELOW.
 - · IN THE EVENT OF A CRITICAL OPERATION SUCH AS SEARCH AND RESCUE, DISASTER RELIEF, AIRCRAFT MECHANICAL PROBLEM FOR A MISSION CRITICAL AIRCRAFT, OR OTHER EMERGENCY, REGARDLESS OF THE TIME, THE CONTRACTOR SHALL IMMEDIATELY PROVIDE FOR PASSAGE OF ANY AIRCRAFT, WITH A MAXIMUM 15 MINUTE DELAY FROM TIME OF NOTIFICATION BY THE ENGINEER, AIRPORT MANAGER, ATCT OR OPERATIONS CENTER.
- 5. RUNWAY 18-36 TEMPORARY CLOSURE:
- . RUNWAY 18-36 MAY BE CLOSED FROM 6:30 P.M. TO 6:30 A.M. DURING THIS PHASE.
- . PLACE ILLUMINATED RUNNING CLOSURE MARKERS OVER RUNWAY DESIGNATION NUMBERS OF EACH RUNWAY.
- . PLACE HAZARDOUS BARRIERS WITH FLAGS AND FLASHERS AS INDICATED ON PLANS.







REVISION

STATE OF ALASKA **DEPARTMENT OF TRANSPORTATION** AND PUBLIC FACILITIES CENTRAL REGION

KODIAK AIRPORT KODIAK, ALASKA KODIAK AIRPORT RSA EXTENSION, 2014 PROJECT No. 53587 SAFETY PLAN PHASE 28

3/26/2014 SHEET: AD120F 15 AS-BUILT SHEET: a






RUNWAY DESIGNATOR COVER


NOTES:

NOTE 2

- THE DIMENSIONS ARE APPROXIMATE. FIELD VERIFY AND ADJUST AS NECESSARY TO COMPLETELY COVER THE RUNWAY DESIGNATOR.
- RUNWAY DESIGNATOR AND THRESHOLD MARKING COVERS SHALL BE CONSTRUCTED OF MATERIAL SPECIFIED IN SECTION P~671, AND SHALL BE BLACK IN COLOR.
- PLACE AND MAINTAIN RUNWAY DESIGNATOR COVERS AS CONSTRUCTION ALLOWS. COVERS MUST ALSO BE IN PLACE. DURING NON WORKING HOURS.




RUNWAY THRESHOLD MARKING COVER



TIMBER PREPARATION, FLAG AND FLASHER MOUNTING DETAIL NTS

PRE-MANUFACTURED POLYETHYLENE BARRIER
NTS



PAINT DETAIL

HAZARDOUS AREA BARRIERS

NOTES:

- 1. DRILL AND NOTCH TIMBER BEFORE PAINTING.
- 2. REFER TO SECTION 704, HAZARDOUS AREA BARRIER.



BY	DATE	REVISION	


STATE OF ALASKA
DEPARTMENT OF TRANSPORTATION
AND PUBLIC FACILITIES
CENTRAL REGION


KODIAK AIRPORT
KODIAK, ALASKA
KODIAK AIRPORT RSA EXTENSION, 2014
PROJECT No. 53587
AIP No. 3-02-0158-017-2014
SAFETY PLAN
DETAILS

SHEET: AD 15 OF 15 AS-BUILT SHEET:

Street AD 15 Opties C:\prescribing\pen\c053537

Data Ravined: 4/03/2014 2.





3D Max. D+4


-Bedding Material

To be used in unstable areas as directed by the Engineer.

'ALTERNATE'


TYPE "A"

FOUNDATION STABILIZATION



Bottom of embankment


TYPE "B"



SUBGRADE

-Existing Ground

TYPE "C"



TYPE "D" ROCK OR UNYIELDING MATERIAL




SHEET | of |

GENERAL NOTES:

- Sidefill shall be placed and compacted with care under haunches of pipe and shall be brought up evenly and simultaneously on both sides of pipe to I foot above the top of the full length of the pipe.
- Alternate installation methods may only be used when specified or approved by the Engineer.








	MULTIPLE INSTALLATIONS
Dia.	Minimum Space Between Pipes
0" - 42"	24"
48" & Over	1/2 Dia. of pipe or 3', whichever is less.

S = Nominal Pipe Arch Span





			М	ULTIF	LE	IN	STAL	LLA	TIC	NS			
	Жa.				М	Inimu	n Spi	осе	Bet	ween Pipe	s		_
0"	-	42"						24"					_
48"	8	Over	1/2	Span	of	pipe	arch	or	3',	whichever	is	less.	


Date .

	REVISIONS	
Date	Description	Ву
12/1/87	Delete ref. to Specs.	Gdo
4/1/93	Delete Alt. Arch	Gdo
	State of Aleeka	

Department of Transportation & Public Facilities


CULVERT PIPE & ARCH INSTALLATION DETAILS







Embankment level before excavation of trench.

Existing Ground




----- CULVERT PIPE






TYPE "D" ROCK OR UNYIELDING MATERIAL



TYPE "A" FOUNDATION STABILIZATION To be used in unstable areas as directed by the Engineer.



TYPE "B"


ARCH

E-13.00

SHEET | of |

GENERAL NOTES:

- Silt Fence Supports shall be 2-inch PVC pipe reinforced with iron pipe or No. 6 rebar, wood posts, or as approved.
- For Water Installations, secure the ends of the silt fence to the stream bank by staking.
- Use approved Wire Support Mesh to keep filter fabric in place in water installations.
- For Land Installations, fence shall be placed at the toe of embankment or excavation areas, or as directed.
- 5. Fence anchored in standing water shall have the bottom anchored with sandbags or equivalent to prevent gaps.
- Installation and application shall be in accordance with the practices as outlined in the Erosion and Sediment Control Plan.
- 7. Filter fabric shall be overlapped 6 inches at fence supports.
- 8. Filter fabric shall be hung taut, not loose or folded.






— Vertical Support — Horizontal Support — Wire Support Mesh

Filter Fabric

Sand bags filled with washed coarse

aggregate



TRENCH SUPPORT DETAIL

TYPICAL LAND INSTALLATION

Optional Supports when required

Fence Support

Wire Support Fence and/or Filter Fabric

8 Ft. Max. Spacing with wire support fence

5 Ft. Max. Spacing without wire support fence

Fence Supports

5' Max.

Top of Filter Fabric

Ordinary High Water

Filter
Fabric

Sandbags

Wire Support Mesh


TYPICAL WATER INSTALLATION

Top of Bank


(Construction Area)

State of Alaska
Department of Transportation & Public Facilities

SEDIMENT CONTROL
SYSTEM
(SILT FENCE)



KODIAK AIRPORT KODIAK, ALASKA **DEVILS CREEK CULVERT REPAIR** PROJECT No. 57474 **AIRPORT IMPROVEMENT PROGRAM** No. 3-02-0158-01X-201_



VICINITY MAP

NOT TO SCALE

T 28 5. R 20 W SEC. 14, 15, 18, 22 & 23 SEWARD MERIDIAN U.S.G.S. KODIAK (C-2, D-2), ALASKA



REVISION

CONCUR APPROVED APPROVED

> STATE OF ALASKA **DEPARTMENT OF TRANSPORTATION** AND PUBLIC FACILITIES CENTRAL REGION

KODIAK AIRPORT
KODIAK, ALASKA
DEVILS CREEK CULVERT REPAIR
PROJECT No. 57474
AIP No. 3-02-0158-01-201_ TITLES, SIGNATURES, LOCATION MAP

3/18/2014 1 of 9 AS-BUILT SHEET:

INDEX		ANCILLARY D	RAWINGS	APPENDIX DRAWINGS	
SHEET TITLE	SHEET No.	SHEET TITLE	SHEET No.	SHEET TITLE	SHEET
BASIC BID				APPENDIX D	
TITLE, SIGNATURES, LOCATION MAP AND VICINITY MAP	1 2			PHASING PLAN	
LEGEND AND ABBREVIATIONS ESTIMATED QUANTITIES AND ESTIMATING FACTORS	3			PHASE 3	BD1 OF
PROJECT LAYOUT PLAN	5				
DEVILS CREEK CULVERT SITE PLAN DEVILS CREEK CULVERT SECTION	6 7			SAFETY PLAN PHASE 3	BD2 OF
DEVILS CREEK CULVERT REPAIR DETAILS	8	(2. 현급 일) 2014 분인 24 2 2 2 2 2 2 2			502 OF
DEVILS CREEK CULVERT BERM	9	[1] [[[하다 [1] [1] [1] [1] [1] [1] [1]			
		[강마시 [2012년 2월			
경기 가게 되면 되면 되었다. 그런 그리는 그리는 그리는 것		[14] [14] [14] [15] [15] [15] [15] [15]			
		불명 이 시장 등 등 있는 이 사람 중심인			
있는 이게 그는 에게 되었다. 사람은 사이지를 하게 되는데 그렇		내가 되어야 하면 계속하게 되었다.			
					양, 의 왕은 왕은 왕, 그렇게 뭐니?
	ı			[역 기기 경기 경기 기계	이 전 그렇게 되어야 되어 되었습니다. 그런 그는 이 무슨데 하는 그리면 하는 그 그래? 이 모든 것
	-			STANDARD	DRAWINGS
				STANDARD SHEET TITLE	
				SHEET TITLE	SHEET A-1
				SHEET TITLE SYMBOLS	SHEET A-1
				SHEET TITLE SYMBOLS	SHEET A-1
				SHEET TITLE SYMBOLS	SHEET A-1
				SHEET TITLE SYMBOLS	SHEET A-1
				SHEET TITLE SYMBOLS	SHEET A-1
				SHEET TITLE SYMBOLS	SHEET A-1
		of Alexander		SHEET TITLE SYMBOLS	SHEET A-1
		OF ALLEY AND A STATE OF A STATE O		SHEET TITLE SYMBOLS SEDIMENT CONTROL SYSTEM (SILT FENCE)	A-1 E-13.00
		49 11 10 10 10 10 10 10 10 10 10 10 10 10		SHEET TITLE SYMBOLS	A-1 E-13.00
		PREPARED BY: HDR Algsko, Inc. BY DATE	D	SHEET TITLE SYMBOLS SEDIMENT CONTROL SYSTEM (SILT FENCE) STATE OF ALASKA	A-1 E-13.00 KODIAK AIRPORT DATE: 3/18/2

LEGE	END		ABBREVIATIONS	ABBREVIATIONS
ESCRIPTION	N EXISTING PROPOSED			
UILDING			AOA AIRCRAFT OPERATIONS AREA	RT RIGHT OFFSET
ONSTRUCTION LICENSE BOUNDARY				그 그 이 계속되어 그리면서 마셨어요? 그렇게 얼마를 보았다면 모양이 없다고 뭐라고 되었다.
ONTROL BOX	[6]		ARFF AIRPORT RESCUE FIRE FIGHTING	RW RUNWAY
JLVERT	c====	10 mg	ASDA ACCELERATE STOP DISTANCE AVAILABLE	SD STORM DRAIN
TCH WITH DRAINAGE FLOW DIRECTION DGE OF PAVEMENT			ATCT AIR TRAFFIC CONTROL TOWER	S.F. SQUARE FEET
INCE	xx_	xx	AWOS AUTOMATED WEATHER OBSERVING SYSTEM	SPCD SAFETY PLAN COMPLIANCE DOCUMENT
EOTEXTILE SEPARATION			CABC CRUSHED AGGREGATE BASE COURSE	SS SANITARY SEWER
RADE BREAK		GB	CL CENTER LINE	
ASE LOT BOUNDARY			이 이는 집에서 다시나이 나는 사람들은 아름이 얼마를 가장하는데 되었다.	STA STATION
EAN HIGH WATER KISTING GROUND			1lb./cu.ft. POUND PER CUBIC FOOT	TODA TAKE OFF DISTANCE AVAILABLE
BJECT FREE AREA	OFA		C.S. CONTINGENT SUM	TORA TAKE OFF RUN AVAILABLE
BJECT FREE ZONE	OFZ		CSPP CONSTRUCTION SAFETY PHASING PLAN	TW TAXIWAY
₩	0000		C.Y. CUBIC YARD	OFA OBJECT FREE AREA
VEMENT MARKING			E EASTING	OFZ OBJECT FREE ZONE
ROJECT EARTHWORK AND GRADING LIMITS ROPERTY BOUNDARY			그 그 그리다 아이들은 얼마에 그를 잃었다면 하는 그릇을 가지 않는데 살아갔다.	그 - [- 하스티스 - 사람이 : [[[[[[[[[[[[[[[[[[
EIL	8		EB EAST BAY OF BOX CULVERT	OHE OVERHEAD ELECTRIC
PRAP / ARMOR		1 Jan 1 1 2 2	ELEV ELEVATION	UGE UNDERGROUND ELECTRIC
DADWAY	========		EMAS ENGINEERED MATERIAL ARRESTING SYSTEM	UGTel UNDERGROUND TELECOMMUNICATIONS
DIATING BEACON	XX		EOP EDGE OF PAVEMENT	USCG UNITED STATES COAST GUARD
JNWAY PROTECTION ZONE JNWAY SAFETY AREA	RPZ		FASBC FOAMED ASPHALT STABILIZED BASE COURSE	VASI VISUAL APPROACH SLOPE INDICATOR
INWAY THRESHOLD MARKERS		0000		요리 맛이다고 있는데 이렇게 이번 얼마가지 않는데 그를 살을 했다"라고 말
GN	-0-	-	FOD FOREIGN OBJECT DEBRIS/ FOREIGN OBJECT DAMAGE	WB WEST BAY OF BOX CULVERT
OPE VALUE AND DIRECTION		XXXX.	GB GRADE BREAK	Wx WEATHER
POT ELEVATION		XXX	HDPE HIGH DENSITY POLYETHYLENE	
DE OF SLOPE FILL			HMA HOT MIXED ASPHALT	
CUT			LDA LANDING DISTANCE AVAILABLE	[발생기(Sp. 발문학원 전투원 하기 : [발문화]회 (학교 기계 : 학교회 소)
SI	0.0		L.F. LINEAR FOOT	
	4		그 그 전쟁 그림아이라고 가게 되었다면서 그 그리고 하다고 말라.	
ND CONE UNLIGHTED	+		LS. LUMP SUM	그 [문화] 공항 그렇게 되었다. 그는 그는 그를 가장하는 것이 없다.
ND CONE AND SEGMENTED CIRCLE	400	402	LT LEFT OFFSET	DETAIL NUMBER
	£	r.	MHW MEAN HIGH WATER	1 XX - SMEET WHERE DETAIL
			MPH MILES PER HOUR	IS LOCATED
			N NORTHING	DETAIL MARKER
			N.T.S. NOT TO SCALE	SECTION LETTER
II MES				FLAG INDICATES DIRECTION OF SECTION CUT
ILMES	55		RAP RECYCLED ASPHALT PAVEMENT	SHEET WHERE SECTION
NITARY SEWER LINE WITH MANHOLE			RPZ RUNWAY PROTECTION ZONE	IS LOCATED WITH THE RESERVE OF THE PROPERTY OF
DRM DRAIN WITH FIELD INLET MANHOLE	SD SD		RSA RUNWAY SAFETY AREA	SECTION CUT MARKER
ITER VALVE	0-3 ash			
TER LINE WITH MANHOLE	₹— w——		SE OF ALM	[중시][일] 살림 성시[경임기 (경기][일리 #사원원로 [사유 수 대가 다시.
				중 시계 살았다. 전에 가는 이 경험을 하지 않는 그리고 있다면 하는데 하는데 되었다.
			2497	STATE OF ALASKA KODIAK AIRPORT DATE: 3/18/2
			2 Dirt L Creday C C 10561	DEPARTMENT OF TRANSPORTATION DEVIS COPY OF VEHICLE STATES
			Marian Marian	AND PUBLIC FACILITIES AP No. 3-02-0158-01-201_ AS-BUILT S
		1	PREPARED BY: HDR Alaska, Inc. BY DATE REVISION	CENTRAL REGION LEGEND AND ABBREVIATIONS OF

ESTIMATED QUANTITIES

No.	ITEM	UNIT	QUANTIT
G-100a	MOBILIZATION AND DEMOBILIZATION	L.S.	ALL REQ'D
G-115a	WORKER MEALS AND LODGING, OR PER DIEM	L.S.	ALL REQ'D
G-130a	FIELD OFFICE	L.S.	ALL REQ'D
G-130b	FIELD LABORATORY	L.S.	ALL REQ'D
G-130j	ENGINEERING COMMUNICATIONS	C.S.	ALL REQ'D
G-135a	CONSTRUCTION SURVEYING BY THE CONTRACTOR	L.S.	ALL REQ'D
G-135b	EXTRA THREE PERSON SURVEYING PARTY	HOUR	20
G-200a	CONTRACTOR QUALITY CONTROL PROGRAM	L.S.	ALL REQ'D
G-300a	CPM SCHEDULING	L.S.	ALL REQ'D
G-700a	AIRPORT FLAGGER	C.S.	ALL REQ'D
P-152ae	DITCH LINING	TON	320
P-152i(2)	BORROW (<10% No. 200)	TON	1,355
P-152r	SUBGRADE PREPARATION	S.Y.	1,280
P-157a	EROSION, SEDIMENT, AND POLLUTION CONTROL ADMINISTRATION	L.S.	ALL REQ'D
P-157b	TEMPORARY EROSION, SEDIMENT, AND POLLUTION CONTROL	C.S.	ALL REQ'D
P-157f	WITHHOLDING	C.S.	ALL REQ'D
P-157g	SWPPP MANAGER	L.S.	ALL REQ'D
P-160a	EXCAVATION OF PAVEMENT (AC)	S.Y.	320
P-161b	RECYCLED ASPHALT PAVEMENT	C.Y.	30
P-164a	HYDRODEMOLITION	S.Y.	1,600
P-164b	SCARIFICATION	S.Y.	700
P-165a(2)	REMOVAL OF STRUCTURES (DEVILS CREEK)	L.S.	ALL REQ'D
P-209b	CRUSHED AGGREGATE BASE COURSE	TON	200
P-511a	MICROSILICA MODIFIED CONCRETE	S.Y.	1,600
P-511b	EPOXY-BONDED EPOXY MORTAR	S.Y.	750
P-610g	STEEL REINFORCEMENT	L.F.	7,000

ESTIMATING FACTORS

ITEM DESCRIPTION ESTIMATING FACTOR

HOT MIX ASPHALT	150 lb./cu.ft.
ASPHALT CEMENT	5.5%
CRUSHED AGGREGATE BASE COURSE	145 lb./cu.ft.
SUBBASE	142 lb./cu./ft.
DITCH LINING	130 lb./cu.ft.





Inc.	DI	DATE	REVISION
Inc.	DV	DATE	DEMON
1			
	\square		
	\vdash		


STATE OF ALASKA
DEPARTMENT OF TRANSPORTATION
AND PUBLIC FACILITIES
CENTRAL REGION


KODIAK AIRPORT
KODIAK, ALASKA
DEVILS CREEK CULVERT REPAIR
PROJECT NO. 57474
AIP NO. 3-02-0158-01-201_
ESTIMATED QUANTITIES
AND ESTIMATING FACTORS

3/18/2014					
HEET:	OF	9			
S-BU	LT S	HEET:			
	ar				









EPOXY-BONOED EPOXY MORTAR EPOXY-BONDED EPOXY MORTAR 3" COVER OVER SEWER PIPE MICROSILICA -MICROSILICA MODIFIED CONCRETE NS. CONCRETE

CULVERT REPAIR DETAIL

NOTES:

- 1. REMOVE EXISTING AND DETERIORATED CONCRETE TO A MINIMUM ¾" BELOW TOP LAYER OF TRANSVERSE REINFORCING STEEL OR TO DEPTH OF SOUND CONCRETE, WHICHEVER IS GREATER.
- 2. SCARIFY AREAS OF DETERIORATED CONCRETE.
- CLEAN EXPOSED REINFORCING STEEL OF CORROSION, RUST.
- 4. REPAIR REINFORCING STEEL WHERE RUST, CORROSION OR ABRASION HAS REOUCED REINFORCING STEEL CROSS—SECTIONAL AREA TO LESS THAN 80% OF ORIGINAL REINFORCING STEEL CROSS-SECTIONAL AREA. (SEE ITEM 610)
- 5. REPAIR OF REINFORCING STEEL SHALL CONSIST OF SECURELY ATTACHING A #4 BAR OF REINFORCING STEEL TO THE DAMAGED BAR. THE BAR WILL RUN THE FULL WIDTH OF THE HYDRO DEMOLITION AREA. IN AREAS OF MULTIPLE DAMAGED BARS, EVERY SECOND BAR SHALL BE REPAIRED.
- 6. PLACE NEW CONCRETE SO SURFACE IS 3"
 ABOVE TOP OF TRANSVERSE REINFORCING STEEL.

LEGEND

HYDRO DEMOLITION

SCARIFICATION

MICROSILICA MODIFIED CONCRETE

EPOXY-BONDED EPOXY MORTAR




PARED BY: HDR Alaska, Inc.	BY	DATE	REVISION
IN THE COLUMN TO			
American American			
10 4014			
John G. Wolf			
Me ALLOR			
* 49H *			

STATE OF ALASKA **DEPARTMENT OF TRANSPORTATION** AND PUBLIC FACILITIES CENTRAL REGION

KODIAK AIRPORT KODIAK, ALASKA DEVILS CREEK CULVERT REPAIR PROJECT NO. 57474 AIP No. 3-02-0158-01-201_ DEVILS CREEK CULVERT REPAIR DETAILS

3/18/2014 SHEET: 8 OF 9 AS-BUILT SHEET: OF



- CONSTRUCTION SUMMARY:

 1. WORK ASSOCIATED WITH THIS PHASE INCLUDES, BUT IS NOT LIMITED TO, THE FOLLOWING:
 - . REPAIR INTERIOR OF PCC BOX CULVERT
 - CONSTRUCT A DIKE AROUND THE ENTRANCE TO THE BOX CULVERT TO RAISE HYDRAULIC HEAD OF THE CREEK TO INCREASE FLOW THROUGH THE CULVERT
- 2. AREAS CLOSED TO AIRCRAFT OPERATIONS

RUNWAY 7-25 AND TAXIWAYS D AND F SHALL REMAIN OPEN AT ALL TIMES.

3. DURATION OF CLOSURES

RUNWAY 7-25 AND TAXIWAYS D AND F SHALL REMAIN OPEN AT ALL TIMES.

4. Taxi Routes

TAXI ROUTES WILL NOT BE CHANGEO.

WHILE CONSTRUCTION ACTIVITY IS UNDER WAY, LARGE AIRCRAFT (GREATER THAN 12,500 POUNDS) MAY NOT MAKE A RIGHT TURN WHILE TAXING FROM THE COMMERCIAL APRON VIA TAXIWAY F ONTO RUNWAY 7-25 FOR BACKTAXI TO RUNWAY 7 TO AVOID JET/PROP BLAST TO THE CONSTRUCTION AREA AT DEVILS CREEK. TAXIWAY F AND TAXIWAY D SHALL BE USED.

5. ARFF ACCESS ROUTES

ARFF ACCESS ROUTES WILL NOT BE AFFECTED DURING THIS PHASE.

6. CONSTRUCTION ACCESS AND HAUL ROUTES

ACCESS AND HAUL ROUTES SHALL BE GENERALLY AS FOLLOWS:

THE PRIMARY ACCESS ROUTE TO THE SOUTH END OF THE DEVILS CREEK CULVERT WILL BE FROM REZANOF DRIVE WEST, PROCEED VIA BITH STREET AND G AVENUE TO THE SECURITY GATE ADJACENT TO THE USCG ARFF FACILITY. ENTER THE AOA AND PROCEED WEST ALONG SERVICE ROAD SOUTH OF TAXIWAY O AND ENTER PROJECT AREA ALTERNATE ROUTE IS THROUGH THE DEVILS CREEK GATE USING FLAGGERS AT ACCESS CONTROLS SIMILAR TO THE RSA EXTENSION PROJECT.

THE ACCESS AND HAUL ROUTE TO THE NORTH END OF THE DEVILS CREEK CULVERT WILL BE FROM REZANOF DRIVE WEST, PROCEED FROM THE TERMINAL ENTRANCE ROAD TO THE DEVILS CREEK SERVICE ROAD. ENTER THE AGA THROUGH THE GATE AT DEVILS CREEK AND THEN PROCEED TO THE PROJECT AREA ON THE RIGHT.

7. IMPACTS ON NAVAIDS

NO NAVAIDS WILL BE AFFECTED BY THIS PHASE.

8. LIGHTING AND MARKING CHANGES


THERE WILL BE NO LIGHTING OR MARKING CHANGES DURING THIS PHASE.

9. AVAILABLE RUNWAY LENGTH

RUNWAY LENGTHS INCLUDED IN PHASES 1A AND 1B WILL APPLY.

10. COORDINATION WITH OTHER PROJECTS

THIS PHASE IS BEING PERFORMED UNDER A CONSTRUCTION CONTRACT INCLUDING THE KODIAK AIRPORT RSA EXTENSION, PROJECT NO. 53587, ANO KOOIAK AIRPORT DEVILS CREEK CULVERT REPAIR, PROJECT NO. 57474. THE CONSTRUCTION SAFETY AND PHASING PLAN INCLUDES BOTH PROJECTS AND PROVISIONS FOR THE PLAN APER APPLICABLE TO ROTAL PROJECTS. ARE APPLICABLE TO BOTH PROJECTS.



LEGEND

CONSTRUCTION AREA

 $\times\!\!\times\!\!\times$

CONTRACTOR STAGING AREA


.......

HAZARD AREA BARRIERS

HAUL ROUTE

PHASE 3 SAFETY PLAN NOTES:

- KEEP ALL WORKERS, EQUIPMENT AND MATERIALS OUTSIDE OF THE ACTIVE RUNWAY SAFETY AREA, NAVAID CRITICAL AREAS, AND APPROACH SURFACES DURING AIRCRAFT OPERATIONS, AND ONLY ENTER THESE AREAS AS REQUIRED AND AS APPROVED.
- KEEP ALL WORKERS, EQUIPMENT, AND MATERIALS OUTSIDE OF THE TAXIMAY SAFETY AREAS AND TAXIWAY OBJECT FREE AREAS WHILE TAXIWAYS ARE OPEN TO AIRCRAFT. ALL TAXIMG AIRCRAFT HAVE THE RIGHT OF WAY.
- 3. USE THE DESIGNATED HAUL ROUTES FOR THIS PHASE AS SHOWN. ALTERNATE HAUL ROUTES MUST BE APPROVED AND DEPICTED IN THE APPROVED SPCD.
- PROVIDE AN AIRPORT FLAGGER IF HAULING ACROSS AN ACTIVE TAXIWAY AND/OR ACTIVE RUNWAY AND IS APPROVED AND INCLUDED IN THE APPROVED SPCD.
- 5. PROVIDE A GATE GUARD IF ANY GATE REMAINS OPEN DURING CONSTRUCTION ACTIVITIES.
- 6. TEMPORARY CLOSURE OF ANY RUNWAY OR TAXIWAY MUST BE DEPICTED IN THE APPROVED SPCD. COORDINATE WITH THE AIRPORT MANAGER, FAA, AIRPORT TENANTS AND OPERATORS, THROUGH THE ENGINEER AT LEAST 45 DAYS IN ADVANCE OF ACTUAL CLOSURES. REFER TO THE SCPP FOR ALLOWED CLOSURE DURATIONS.
- 7. HAZARDOUS AREA BARRIERS ARE SHOWN AT APPROXIMATE LOCATIONS. ADJUSTMENTS OR ADDITIONAL LOCATIONS MAY BE REQUIRED. RELOCATE BARRIERS AS DIRECTED BY THE ENGINEER.
- 8. PROVIDE PICK UP BROOM TRUCK (STREET SWEEPER), OR OTHER EQUIPMENT AS APPROVED FOR CONTROL OF FOD ON ACTIVE SURFACES. CLEAN ACTIVE SURFACES OF FOD IMMEDIATELY UPON DISCOVERY OR NOTIFICATION. CLEAN AFFECTED RUNWAY AND TAXIWAY SURFACES PRIOR TO REOPENING.
- 9. ARFF MUST HAVE ACCESS TO ENTIRE AIRPORT DURING EMERGENCIES. MAINTAIN SUITABLE CORRIDORS AND COORDINATE ACCESS WITH ARFF PERSONNEL THROUGH THE ENGINEER AS REQUIRED.
- 10. RUNWAY 7-25 AND TAXIWAYS D AND F SHALL REMAIN OPEN AT ALL TIMES
- 11. COORDINATION WITH OTHER PROJECTS
 THIS PHASE IS BEING PERFORMED UNDER A CONSTRUCTION CONTRACT INCLUDING THE KODIAK AIRPORT RSA EXTENSION, PROJECT NO. 53587, AND KODIAK AIRPORT DEVILS CREEK CULVERT REPAIR, PROJECT NO. 57474. THE CONSTRUCTION SAFETY AND PHASING PLAN INCLUDES BOTH PROJECTS. PROVISIONS FOR THE PLAN ARE APPLICABLE TO BOTH PROJECTS.



CONSTRUCTION AREA


CONTRACTOR STAGING AREA

HAZARD AREA BARRIERS

HAUL ROUTE

LEGEND

FLAGGER




E-13.00

SHEET

GENERAL NOTES:

- Silt Fence Supports shall be 2-inch PVC pipe reinforced with iron pipe or No. 6 rebar, wood posts, or as approved.
- 2. For Water Installations, secure the ends of the silt fence to the stream bank by staking.
- 3. Use approved Wire Support Mesh to keep filter fabric in place in water installations.
- 4. For Land Installations, fence shall be placed at the toe of embankment or excavation areas, or as directed.
- Fence anchored in standing water shall have the bottom anchored with sandbags or equivalent to prevent gaps.
- Installation and application shall be in accordance with the practices as outlined in the Erosion and Sediment Control Plan.
- 7. Filter fabric shall be overlapped 6 inches at fence supports.
- 8. Filter fabric shall be hung taut, not loose or folded.




— Vertical Support — Horizontal Support — Wire Support Mesh

-Filter Fabric




Wire Support Fence and/or Filter Fabric



Optional Supports when required

Fence Suppor

TYPICAL LAND INSTALLATION



Top of Bank (Construction Area)

