

INTERIOR LIGHT FIXTURE SCHEDULE									
SYMBOL	TYPE	LOAD	VOLT.	LAMP		DESCRIPTION	MANUF.	MODEL NO.	
				NUM.	TYPE				
	CAA	27	277	1	F241SHO 4100K	28" WIDE FLUORESCENT OVER MIRROR LIGHT FIXTURE WITH OPAL WHITE GLASS DIFFUSER AND GRAY METALLIC FINISH.	BLAUET OR APPROVED EQUAL	1327-03-36-63	
	COA	54	277	2	26W CFO 4100K	6" 2-LAMP, RECESSED, COMPACT FLUORESCENT DOWNLIGHT WITH HORIZONTAL LAMPING, CLEAR LENS, CLEAR ALZAK SEMI-DIFFUSE LOW INDESCENT REFLECTOR AND ELECTRONIC BALLAST.	PRESCOLITE GOTHAM LIGHTOLIER OMEGA LIGHTING	LF8 SERIES AF SERIES OMS SERIES	
	COB	54	277	2	26W CFO 4100K	SAME AS TYPE "COA". SHADING INDICATES FIXTURE ON EMERGENCY CIRCUIT.	PRESCOLITE GOTHAM LIGHTOLIER OMEGA LIGHTING	LF8 SERIES AF SERIES OMS SERIES	
	COD	27	277	1	26W CFO 4100K	SEMI-RECESSED, COMPACT FLUORESCENT DOWNLIGHT WITH 4.4" DIAMETER X 5.5" LONG WHITE OPAL CYLINDRICAL GLASS DIFFUSER AND WHITE TRIM RING AND ELECTRONIC BALLAST.	LOUIS POULSEN	BALLERUP SERIES	
	COH	27	277	1	26W CFO 4100K	SAME AS TYPE "COD". SHADING INDICATES FIXTURE ON EMERGENCY CIRCUIT.	LOUIS POULSEN	BALLERUP SERIES	
	COK	52	277	2	26W CFO 4100K	SAME AS TYPE "COA" EXCEPT PROVIDE BLACK BAFFLE AND DIMMING BALLAST.	PRESCOLITE GOTHAM LIGHTOLIER OMEGA LIGHTING	LF8 SERIES AF SERIES OMS SERIES	
	COM	35	277	1	32W CFR 4100K	4-1/2" SQUARE RECESSED, COMPACT FLUORESCENT DOWNLIGHT, CLEAR ALZAK SEMI-DIFFUSE LOW INDESCENT REFLECTOR AND ELECTRONIC BALLAST.	KURT VERSEN LIGHTOLIER SPECTRUM	H2 SERIES 4X4 SERIES D4HSO SERIES	
	CON	35	277	1	32W CFR 4100K	SAME AS TYPE "COM". SHADING INDICATES FIXTURE ON EMERGENCY CIRCUIT.	KURT VERSEN LIGHTOLIER SPECTRUM	H2 SERIES 4X4 SERIES D4HSO SERIES	
	COO	35	277	1	32W CFR 4100K	8" COMPACT FLUORESCENT "DEAD FRONT" DOWNLIGHT WITH HORIZONTAL LAMPING, WHITE TRIM, RADIAL CLEAR POLYCARBONATE LENS AND ELECTRONIC BALLAST. U.L. LISTED FOR WET LOCATIONS.	KIRLIN LIGHTOLIER	FR8-05032 SERIES 1175H SERIES	
	COP	168	277	1	150W CMH 18 G12	14-1/2" DIAMETER X 28" TALL PENDANT LIGHT FIXTURE WITH CLEAR POLYCARBONATE OUTER CONE, SPUN ALUMINUM INTERNAL SHADE, MEDIUM REFLECTOR AND DIE-CAST ALUMINUM RINGS, STAINLESS STEEL AIRCRAFT CABLE AND GREY POWER CORD.	LOUIS POULSEN	LP CHARISMA KING SERIES	
	COR	35	277	1	32W CFR 4100K	8" DIAMETER BY 12" DEEP SURFACE MOUNTED COMPACT FLUORESCENT CYLINDER WITH ALUMINUM HOUSING, CLEAR ALZAK REFLECTOR AND ELECTRONIC BALLAST, FINISH PER ARCHITECT.	PRESCOLITE	CFRC3212B SERIES	
	COX	1	12	1	1W LED WHITE	4-1/8" ROUND X 7/8" DEEP WHITE LED STEP LIGHT WITH 30 DEGREE DISTRIBUTION, 45 DEGREE ANGLE BRACKET, CLEAR GLASS LENS, STAINLESS STEEL FACEPLATE AND REMOTE DRIVER.	MP LIGHTING	LE002 SERIES	
	CPA	50	120	1	50W HALOGEN T4 GY35	SEMI-RECESSED DECORATIVE DOWNLIGHT WITH 1.7" DIAMETER X 2.1" LONG WHITE OPAL CYLINDRICAL GLASS DIFFUSER AND WHITE TRIM RING.	LOUIS POULSEN	BALLERUP MICRO SERIES	
	CPB	46	277	1	42W CFR 4100K	10.5" DIAMETER X 14.5" TALL COMPACT FLUORESCENT PENDANT LIGHT FIXTURE WITH CLEAR ACRYLIC OUTER DIFFUSER WITH AN ETCHED LOWER BAND, OPAL ACRYLIC CYLINDRICAL INTERNAL DIFFUSER AND CANOPY FINISH PER ARCHITECT. PROVIDE WITH DIMMING BALLAST.	BETA-CALCO	KIORA 44-0902 SERIES	
	CPB1	46	120	1	42W CFR 4100K	SAME AS TYPE "CPB" EXCEPT 120 VOLT.	BETA-CALCO	KIORA 44-0902 SERIES	
	CPB2	46	277	1	42W CFR 4100K	SAME AS TYPE "CPB3". SHADING INDICATES FIXTURE ON EMERGENCY CIRCUIT.	BETA-CALCO	KIORA 44-0902 SERIES	
	CPB3	46	277	1	42W CFR 4100K	SAME AS TYPE "CPB" EXCEPT NON-DIMMING.	BETA-CALCO	KIORA 44-0902 SERIES	
	CPC	250	120	1	250W T-4 MN CAN FROSTED TUNGSTEN HALOGEN	8.75" DIAMETER X 14" TALL PENDANT MOUNTED CYLINDER WITH MOCHA CONE. FINISH PER ARCHITECT.	KURT VERSEN	L394-H-P5-ES	
	CND	35	277	1	32W CFR 4100K	COMPACT FLUORESCENT GREY WALL BRACKET WITH OPAL GLASS GLOBE AND NON-METALLIC WIREGUARD. U.L. LISTED FOR WET LOCATIONS.	CANLET RIG-A-LITE PHOENIX EXCELINE	GFMF SERIES CVO SERIES VAPORITE SERIES KALEIDOSCOPE SERIES	
	CND1	35	120	1	32W CFR 4100K	SAME AS TYPE "CND" EXCEPT 120 VOLT.	CANLET RIG-A-LITE PHOENIX EXCELINE	GFMF SERIES CVO SERIES VAPORITE SERIES KALEIDOSCOPE SERIES	
	CNG	27	277	1	F391SHO 4100K	38" TALL VERTICALLY MOUNTED FLUORESCENT LIGHT FIXTURE WITH OPAL WHITE GLASS DIFFUSER AND GRAY METALLIC FINISH.	BLAUET OR APPROVED EQUAL	1335-03-36-62	
	FBD	24	277	2	F01718XPS 4100K	2'X2', 2-LAMP RECESSED INDIRECT FLUORESCENT LIGHT FIXTURE WITH MATTE WHITE PERFORATED METAL LIGHT BASKET WITH OPAL ACRYLIC OVERLAY AND TOP DUST COVER. 5-3/4" DEEP DIE-FORMED STEEL HOUSING WITH WHITE ENAMEL FINISH, PAINTED AFTER FABRICATION.	COLUMBIA LITHONIA DAYBRITE	STRATUS SERIES AVANTE SERIES ARSOD SERIES	
	FBD1	72	277	2	F40TT 4100K	2'X2', 2-LAMP RECESSED DIRECT/INDIRECT FLUORESCENT LIGHT FIXTURE WITH 16-CELL SINGLE ROW MATTE LOUVERED CENTER BASKET WITH OPAL INLAY AND TOP DUST COVER. 5-1/4" DEEP STEEL HOUSING WITH WHITE ENAMEL FINISH.	ZUMTOBEL STAFF LIGHTOLIER	SYNTO IS SERIES ALETTA ALZTS SERIES VOICE SERIES	
	FBE	24	277	2	F01718XPS 4100K	SAME AS TYPE "FBD". SHADING INDICATES FIXTURE ON EMERGENCY CIRCUIT.	COLUMBIA LITHONIA DAYBRITE	STRATUS SERIES AVANTE SERIES ARSOD SERIES	
	FBG	71	277	3	F03278XPS 4100K	2'X4', 3-LAMP RECESSED DIRECT/INDIRECT FLUORESCENT LIGHT FIXTURE WITH ACRYLIC ENCLOSED SQUARE "LIGHT BASKET".	LEDALITE PINNACLE	VECTRA SERIES MAGO SERIES	
	FBH	71	277	3	F03278XPS 4100K	SAME AS TYPE "FBG". SHADING INDICATES FIXTURE ON EMERGENCY CIRCUIT.	LEDALITE PINNACLE	VECTRA SERIES MAGO SERIES	
	FDD	52	277	2	F241SHO 4100K	2'X2', 2-LAMP RECESSED INDIRECT FLUORESCENT LIGHT FIXTURE WITH DUAL MATTE WHITE PERFORATED METAL SIDE BASKETS. 5-3/4" DEEP DIE-FORMED STEEL HOUSING WITH WHITE ENAMEL FINISH, PAINTED AFTER FABRICATION.	COLUMBIA LITHONIA DAYBRITE	STRATUS SERIES AVANTE SERIES ALTER SERIES ARSOD SERIES	
	FCJ	120	1	LED		CONTINUOUS CURVABLE LED LIGHT FIXTURE SYSTEM INCLUDING POWER SUPPLIES, MOUNTING CLIPS AND WIRE. FIELD VERIFY EXACT LENGTH.	OR APPROVED EQUAL	LED TECHNOLOGIES OR APPROVED EQUAL	
	FCJA	72	277	2	F40TT 4100K	CONTINUOUS SEAMLESS STRAIGHT FLUORESCENT CONE LIGHT FIXTURE WITH SAW TOOTHED REFLECTOR. FIELD VERIFY EXACT LENGTH.	BELFER LIGHTING OR APPROVED EQUAL	2850-NX2S SERIES	
	FCJA1	72	120	2	F40TT 4100K	SAME AS TYPE "FCJA" EXCEPT 120 VOLT AND PROVIDE WITH DIMMING BALLASTS.	BELFER LIGHTING OR APPROVED EQUAL	2850-NX2S SERIES	
	FGB	142	277	6	F03278XPS 4100K	2'X4', 6-LAMP RECESSED SEALED AND GASKETED FLUORESCENT TROFFER. ONE-PIECE SEAM WELDED HOUSING. WHITE POWDER COAT FINISH. ONE-PIECE 304 STAINLESS STEEL OVERLAP DOOR FRAME WITH CAPTIVE STAINLESS STEEL SCREWS. 1/2" THICK ACRYLIC PRISMATIC LENS. SILICONE GASKETING BETWEEN DOOR FRAME AND HOUSING. CLOSED CELL NEOPRENE GASKETING BETWEEN DOOR FRAME AND HOUSING AND BETWEEN FLANGE AND CEILING. U.L. LISTED FOR WET LOCATIONS. SUITABLE FOR USE IN CLASS 100-100,000 CLEAN ROOMS. PROVIDE FIXTURE WITH EMERGENCY BATTERY BACKUP.	KENALL KTR KURZON	CSE SERIES KTR SERIES KL SERIES	
	FGH	142	277	6	F03278XPS 4100K	2'X4', 6-LAMP RECESSED SEALED AND GASKETED FLUORESCENT TROFFER. ONE-PIECE SEAM WELDED HOUSING. WHITE POWDER COAT FINISH. ONE-PIECE 304 STAINLESS STEEL OVERLAP DOOR FRAME WITH CAPTIVE STAINLESS STEEL SCREWS. 1/2" THICK ACRYLIC PRISMATIC LENS. SILICONE GASKETING BETWEEN DOOR FRAME AND HOUSING. CLOSED CELL NEOPRENE GASKETING BETWEEN DOOR FRAME AND HOUSING AND BETWEEN FLANGE AND CEILING. U.L. LISTED FOR WET LOCATIONS. SUITABLE FOR USE IN CLASS 100-100,000 CLEAN ROOMS.	KENALL KTR KURZON	CSE SERIES KTR SERIES KL SERIES	
	FGM	71	277	3	F03278XPS 4100K	10-7/8" X 4", 3-LAMP SURFACE MOUNTED SEALED AND GASKETED FLUORESCENT LIGHT FIXTURE. U.L. LISTED FOR WET LOCATIONS. FIXTURE SHALL BE MOUNTED TO UNSTRUT.	MORLITE	LPL 2000 SERIES	
	FGM1	71	277	3	F03278 4100K	SAME AS TYPE "FGM" EXCEPT SURFACE ON CEILING.	MORLITE	LPL 2000 SERIES	
	FGM2	71	277	3	F03278 4100K	SAME AS TYPE "FGM" EXCEPT PROVIDE DIMMING BALLAST.	MORLITE	LPL 2000 SERIES	
	FGN	71	277	3	F03278 4100K	SAME AS TYPE "FGM". SHADING INDICATES FIXTURE ON EMERGENCY CIRCUIT.	MORLITE	LPL2000 SERIES	
	FGN1	71	277	3	F03278 4100K	SAME AS TYPE "FGM1". SHADING INDICATES FIXTURE ON EMERGENCY CIRCUIT.	MORLITE	LPL 2000 SERIES	
	FGN2	32	277	1	F03278 4100K	10-7/8" X 4", 1-LAMP SURFACE MOUNTED SEALED AND GASKETED FLUORESCENT LIGHT FIXTURE. U.L. LISTED FOR WET LOCATIONS.	MORLITE	LPL 2000 SERIES	
	FGN3	32	277	1	F03278 4100K	SAME AS TYPE "FGN2" EXCEPT PROVIDE WITH DIMMING BALLAST.	MORLITE	LPL 2000 SERIES	
	FGN4	114	277	4	F03278 3500K	10-7/8" X 4", 4-LAMP SURFACE MOUNTED SEALED AND GASKETED FLUORESCENT LIGHT FIXTURE. U.L. LISTED FOR WET LOCATIONS.	MORLITE	LPL 2000 SERIES	
	FGN8	228	277	8	F03278 3500K	SAME AS TYPE "FGN4" EXCEPT 8 LAMP, 8-LAMP FIXTURE.	MORLITE	LPL 2000 SERIES	
	FGNR	228	277	8	F03278 3500K	SAME AS TYPE "FGN8" EXCEPT PROVIDE WITH THREE BALLASTS AND TWO RED FILM LAMP COVERS FOR THE TWO CENTER LAMPS.	MORLITE	LPL 2000 SERIES	
	FGNR1	114	277	4	F03278 3500K	SAME AS TYPE "FGNR" EXCEPT PROVIDE WITH TWO BALLASTS AND TWO RED FILM LAMP COVERS FOR THE TWO CENTER LAMPS.	MORLITE	LPL 2000 SERIES	
	FIA	228	277	8	F03278 4100K	16", 8-LAMP PENDANT MOUNTED LINEAR DIRECT/INDIRECT FLUORESCENT LIGHT FIXTURE WITH STEEL HOUSING, BOTTOM PARALLEL BLADE CENTER LOUVER, SOFT TOP OPTICS, FLAT END CAPS, DUAL CIRCUIT (LEFT/RIGHT) AND FULLY ADJUSTABLE AIRCRAFT CABLE MOUNTING. FINISH PER ARCHITECT.	FINELINE OR APPROVED EQUAL	SERIES 16	
	FIA1	60	277	2	F28T5 4100K	PENDANT MOUNTED LINEAR DIRECT/INDIRECT FLUORESCENT LIGHT FIXTURE WITH STEEL HOUSING, BOTTOM PARALLEL BLADE CENTER LOUVER WITH ACRYLIC LENS DIFFUSER AND TOP DUST COVER. FINISH PER ARCHITECT. FIELD VERIFY EXACT LENGTH.	FOCAL POINT	LOUVER TWELVE SERIES THIRVE HIGH PERF. OVAL SERIES	
	FIA2	176	277	2	F541SHO 3500K	PENDANT MOUNTED LINEAR DIRECT/INDIRECT FLUORESCENT LIGHT FIXTURE. FINISH PER ARCHITECT. FIELD VERIFY EXACT LENGTH.	FINELINE	X-DIRECT/INDIRECT SERIES 16	
	FIC	60	277	2	F28T5 4100K	SAME AS TYPE "FIA1". SHADING INDICATES FIXTURE ON EMERGENCY CIRCUIT.	FOCAL POINT	LOUVER TWELVE SERIES THIRVE HIGH PERF. 60/40 SERIES	
	FIC1	60	277	2	F28T5 4100K	SAME AS TYPE "FIC". SHADING INDICATES FIXTURE ON EMERGENCY CIRCUIT.	FOCAL POINT	LOUVER TWELVE SERIES THIRVE HIGH PERF. 60/40 SERIES	
	FLA	46	277	2	F03278XPS 4100K	2'X4', 2-LAMP RECESSED FLUORESCENT STATIC TROFFER. 4-1/2" DEEP DIE-FORMED STEEL HOUSING WITH WHITE ENAMEL FINISH, PAINTED AFTER FABRICATION, REGRESSED ALUMINUM DOORFRAME WITH SPRING LOADED LATCHES. 1/2" THICK ACRYLIC PRISMATIC PATTERN 12 LENS.	COLUMBIA LITHONIA LIGHTOLIER DAYBRITE	4FS SERIES 2SP SERIES SPS SERIES DP SERIES	
	FLG	91	277	4	F03278XPS 4100K	2'X4', 4-LAMP RECESSED FLUORESCENT STATIC TROFFER. 4-1/2" DEEP DIE-FORMED STEEL HOUSING WITH WHITE ENAMEL FINISH, PAINTED AFTER FABRICATION, REGRESSED ALUMINUM DOORFRAME WITH SPRING LOADED LATCHES. 1/2" THICK ACRYLIC PRISMATIC PATTERN 12 LENS.	COLUMBIA LITHONIA LIGHTOLIER DAYBRITE	4FS SERIES 2SP SERIES SPS SERIES DP SERIES	

INTERIOR LIGHT FIXTURE SCHEDULE

SCALE NONE 5

INTERIOR LIGHT FIXTURE SCHEDULE									
SYMBOL	TYPE	LOAD	VOLT.	LAMP		DESCRIPTION	MANUF.	MODEL NO.	
				NUM.	TYPE				
	FLM	46	277	2	F03278XPS 4100K	1'X4', 2-LAMP RECESSED FLUORESCENT STATIC TROFFER. 4-1/2" DEEP DIE-FORMED STEEL HOUSING WITH WHITE ENAMEL FINISH, PAINTED AFTER FABRICATION, REGRESSED ALUMINUM DOORFRAME WITH SPRING LOADED LATCHES. 1/2" THICK ACRYLIC PRISMATIC PATTERN 12 LENS.	COLUMBIA LITHONIA LIGHTOLIER DAYBRITE	4FS SERIES 2SP SERIES SPS SERIES DP SERIES	
	FLN	46	277	2	F03278XPS 4100K	SAME AS TYPE "FLM". SHADING INDICATES FIXTURE ON EMERGENCY CIRCUIT.	COLUMBIA LITHONIA LIGHTOLIER DAYBRITE	4FS SERIES 2SP SERIES SPS SERIES DP SERIES	
	FLS1	62	277	1	F541SHO 4100K	3" WIDE X 4' LONG RECESSED, NARROW SLOT FLUORESCENT FIXTURE WITH REGRESSED TRIM, SANDBLASTED ACRYLIC LENS AND MATTE ALUMINUM FINISH.	LINEAR LIGHTING OR APPROVED EQUAL	GM23 SERIES	
	FLS2	126	277	2	F541SHO 4100K	SAME AS TYPE "FLS1" EXCEPT 6 HOUSING WITH 6 CONTINUOUS LENS.	LINEAR LIGHTING OR APPROVED EQUAL	GM23 SERIES	
	FLT1	62	277	1	F541SHO 4100K	SAME AS TYPE "FLS1". SHADING INDICATES FIXTURE ON EMERGENCY CIRCUIT.	LINEAR LIGHTING OR APPROVED EQUAL	GM23 SERIES	
	FLT2	126	277	2	F541SHO 3500K	SAME AS TYPE "FLS2". SHADING INDICATES FIXTURE ON EMERGENCY CIRCUIT.	LINEAR LIGHTING OR APPROVED EQUAL	GM23 SERIES	
	FLV	62	277	1	F541SHO 4100K	3" WIDE X 4' LONG SURFACE MOUNTED NARROW SLOT FLUORESCENT LIGHT FIXTURE WITH SATIN BRUSH ALUMINUM FINISH AND ELECTRONIC BALLAST.	FOCAL POINT ZUMTOBEL STAFF	AVENUE D SERIES ES11-1545-04-U-SM	
	FLV1	60	277	2	F28T5 4100K	4-7/16" WIDE X 8" LONG X 4-3/4" DEEP SURFACE MOUNTED FLUORESCENT DIRECT WALL WASH LIGHT FIXTURE. FINISH PER ARCHITECT.	PINNACLE LIGHTING	EDGE EX44 SERIES	
	FLW	62	277	1	F541SHO 4100K	SAME AS TYPE "FLV". SHADING INDICATES FIXTURE ON EMERGENCY CIRCUIT.	FOCAL POINT ZUMTOBEL STAFF	AVENUE D SERIES ES11-1545-04-U-SM	
	FSC	46	277	2	F03278XPS 4100K	4", 2-LAMP PENDANT MOUNTED FLUORESCENT TURRET STRIP LIGHT FIXTURE. DIE-FORMED STEEL CHANNEL AND SYMMETRIC REFLECTOR WITH 15% UPLIGHT. PROVIDE FIXTURE WITH WIREGUARD.	COLUMBIA LITHONIA LIGHTOLIER PRUDENTIAL	KL SERIES AF SERIES TF SERIES P-200 SERIES	
	FSD	46	277	2	F03278XPS 4100K	SAME AS TYPE "FSC". SHADING INDICATES FIXTURE ON EMERGENCY CIRCUIT.	COLUMBIA LITHONIA LIGHTOLIER PRUDENTIAL	KL SERIES AF SERIES TF SERIES P-200 SERIES	
	FSD1	46	277	2	F03278XPS 4100K	SAME AS TYPE "FSD" EXCEPT PROVIDE WITH EMERGENCY BATTERY BACKUP.	COLUMBIA LITHONIA LIGHTOLIER PRUDENTIAL	KL SERIES AF SERIES TF SERIES P-200 SERIES	
	FSE	91	277	4	F03278XPS 4100K	8", 4-LAMP PENDANT MOUNTED FLUORESCENT TURRET STRIP LIGHT FIXTURE. DIE-FORMED STEEL CHANNEL AND SYMMETRIC REFLECTOR WITH 15% UPLIGHT. PROVIDE FIXTURE WITH WIREGUARD.	COLUMBIA LITHONIA LIGHTOLIER PRUDENTIAL	KL SERIES AF SERIES TF SERIES P-200 SERIES	
	FUC	46	277	2	F03278XPS 4100K	1-LAMP CONTINUOUS RECESSED FLUORESCENT PERIMETER SLOT WALL WASH LIGHT FIXTURE. FIELD VERIFY EXACT LENGTH.	ALTEC LIGHTING	WALL/SLOT-2000 SERIES WALL WASH W44 SERIES	
	FUF	25	277	1	F03278XPS 4100K	4", 1-LAMP FLUORESCENT SOLID FRONT UNDERCABINET LIGHT FIXTURE.	COLUMBIA LITHONIA LIGHTOLIER DAYBRITE	UC SERIES 2UC SERIES TACROSTER II SERIES BUC SERIES	
	FWE	114	277	4	F32T8 4100K	8" WIDE, 4-LAMP WALL MOUNTED DIRECT/INDIRECT FLUORESCENT LIGHT FIXTURE WITH WHITE CROSS BLADE BOTTOM BAFFLE, FLAT END CAPS AND INTEGRAL ELECTRONIC BALLASTS. FINISH PER ARCHITECT.	FINELINE	SERIES 16 KW4M-2-27B-0C-91W-277-FE-FINISH	
	FWE1	186	277	6	F32T8 4100K	SAME AS TYPE "FWE" EXCEPT 12" WIDE, 6-LAMP.	FINELINE	SERIES 16 KW4M-2-27B-0C-91W-277-FE-FINISH	
	FWH	46	277	2	F03278XPS 4100K	4" WIDE, 2-LAMP WALL MOUNTED FLUORESCENT LIGHT FIXTURE. SHADING INDICATES FIXTURE ON EMERGENCY CIRCUIT.	ECLIPSE OR APPROVED EQUAL	ASTRO X12 SERIES	
	HDB	86	277	1	70W MH	SAME AS TYPE "HDC". SHADING INDICATES FIXTURE ON EMERGENCY CIRCUIT.	GUTH OR APPROVED EQUAL	HANDLITER-S SERIES	
	HDC	86	277	1	70W MH	12-1/2" SQUARE SURFACE MOUNTED CANOPY LIGHT FIXTURE WITH POLYCARBONATE PRISMATIC LENS. U.L. LISTED FOR WET LOCATIONS.	GUTH OR APPROVED EQUAL	HANDLITER-S SERIES	
	HDD	86	277	1	70W CMH 18	8"-1/2" X 4-1/2" APERTURE RECESSED METAL HALIDE WALL WASH LIGHT FIXTURE WITH ASTROTRON REFLECTOR, MICROPRISM LENS, CLEAR ALZAK REFLECTOR AND INTEGRAL BALLAST MOUNTED PARALLEL TO WALL. TRIM COLOR PER ARCHITECT.	KURT VERSEN	1450RPM SERIES	
	HEA	375	120	1	375W COMPACT TUNGSTEN HALOGEN	ELLIPSOIDAL LIGHT FIXTURE WITH MOUNTING AND ACCESSORIES T.B.D. BLACK FINISH.	ETC LIGHTING	SOURCE FOUR JR 36 DEGREE 4500K	
	IDB	35	277	1	32W CFR 4100K	6" RECESSED, COMPACT FLUORESCENT WALLWASHER WITH HORIZONTAL LAMPING AND CLEAR ALZAK SEMI-DIFFUSE LOW INDESCENT REFLECTOR. PROVIDE WITH DIMMING BALLAST.	PRESCOLITE GOTHAM LIGHTOLIER OMEGA LIGHTING	AFM SERIES R081 SERIES OMS SERIES	
	IDB1	55	277	1	50W MR16	3-1/2" APERTURE RECESSED, INCANDESCENT ADJUSTABLE ACCENT LIGHT WITH CLEAR SPECULAR REFLECTOR, LOW PROFILE TRIM RING AND INTEGRAL TRANSFORMER. FINISH PER ARCHITECT.	W.A.C. LIGHTING	HR0327-BN SERIES T320-WK000L22 SERIES	
	IDC	1	12	1	1W LED WHITE	4-1/8" ROUND X 7/8" DEEP CEILING MOUNTED ACCENT LIGHT WITH 12 DEGREE DISTRIBUTION, 30 DEGREE ANGLE BRACKET, FROSTED GLASS LENS, STAINLESS STEEL FACEPLATE AND REMOTE DRIVER.	MP LIGHTING	LE002 SERIES	
	IDO	44	277	1	39W CMH 14	9.5" DIAMETER IN-GRADE ADJUSTABLE METAL HALIDE UPLIGHT WITH LOW SURFACE TEMPERATURE, TEMPERED GLASS LENS, SEMI-DIFFUSE LENS, STAINLESS STEEL LENS RING AND REMOTE ELECTRONIC BALLAST.	BEGA	8750MM SERIES	
	IDE	100	120	1	100W A-19	8.5" DIAMETER BY 5.5" DEEP SURFACE MOUNTED INCANDESCENT CYLINDER WITH ALUMINUM HOUSING AND WHITE PAINTED FINISH.	D.M. LIGHTING	6652	
	IDF	100	120	2	100W A-19 15W A-15	TWO COMPARTMENT SURFACE MOUNTED COMBINATION WORK/SAFE LIGHT WITH 10 GA. STEEL HOUSING, PRISMATIC GLASS LENS FOR WORK LIGHT AND RED FILTER FOR SAFE LIGHT.	ALCOCK	SM-2058-2	