

A north arrow pointing upwards with the letter 'N' below it. Below the arrow is a scale bar marked from 0 to 20 feet.

1. CONSTRUCT 6-INCH HIGH PCC CURB AND GUTTER PER CITY OF RAINC STANDARD PLAN NO. 200A.
2. CONSTRUCT 6-INCH HIGH PCC TUCK-IN CURB (SEE SHEET 3, DETAIL 3). CONSTRUCT MONOTONIC PCC CURB/STEWAK WHERE SPECIFIED. (SEE SHEET 3, DETAIL 4 FOR 6-INCH CURB CONDITION OR DETAIL 5 FOR 4-INCH CURB CONDITION).
3. CONSTRUCT 8-INCH THICK PCC REBORN GUTTER. (SEE SHEET 3, DETAIL 7).
4. CONSTRUCT 4-INCH THICK PCC STEWAK PER CITY OF RAINC STANDARD PLAN NO. 200A.
5. CONSTRUCT 4-INCH THICK PCC ACCESS RAMP. (SEE SHEET 4 FOR DETAILS).
6. CONSTRUCT 3.5-INCH THICK ASPHALT CONCRETE PAVEMENT OVER 7-INCH THICK CLASS II AGGREGATE BASE (11-25). (SEE SHEET 4 FOR DETAILS).
7. CONSTRUCT INTERLOCKING PAVEMENTS (SEE LANDSCAPING PLANS).
8. CONSTRUCT PCC STAMS (SEE SHEET 4, DETAIL 2).
9. CONSTRUCT 6-INCH THICK PCC SLAB WITH #4 REBAR AT 18-INCH O.C. BOTH WAYS (MEDIUM BROWN FINISH).
10. CONSTRUCT 6-INCH HIGH PCC ROLLED CURB PER CITY OF RAINC STANDARD PLAN NO. 200A.

15. PUMP AND INSTALL HIGH DENSITY POLYETHYLENE THICK BLOCK (NDS MODEL NO. TT-24 TURFBLOCK) PER MANUFACTURERS SPECIFICATIONS (SEE SHEET 3, DETAIL 10).
16. CONSTRUCT 6-INCH THICK "SHIMMED" PAVING PCC SLAB WITH #4 REBAR AT 18-INCH O.C. BOTH WAYS (SEE LANDSCAPE ARCHITECTS PLANS).
17. CONSTRUCT DEEPENED POOTING, SEE STRUCTURAL DRAWINGS.
18. CONSTRUCT VARIABLE HEIGHT REINFORCED WALL, UNDER SEPARATE PERMIT.
19. CONSTRUCT 3-INCH THICK ASPHALT CONCRETE PAVEMENT OVER 6-INCH THICK CLASS II ASPHALTIC BASE (TYPICAL).
20. CLASS II ASPHALTIC BASE (TYPICAL).

CONSTRUCT 6-INCH HIGH PCC ROLLED CURB PER CITY OF IRVINE STANDARD  
PLAN NO. 200A

11-07-02 OWNER'S REVIEW SET

☐ PRELIMINARY GRADING PERMIT  
☐ PRECISE GRADING PERMIT

GRADING PLAN CHECK # \_\_\_\_\_  
 GRADING PERMIT # \_\_\_\_\_

**SHEET 7 OF 42**

**JOB NO.**