LIGHT FIXTURES LEGEND

- RECESSED EXTERIOR PLASTER ACCESS PANEL — C
- RECESSED STAINLESS STEEL ACCESS PANEL — B
- RECESSED DRYWALL ACCESS PANEL — A
- IN WALL HORN STROBE, GRAINGER #16G826
- EXTERIOR FLOOD LIGHT
- NEW EXTERIOR SCONCE — EXSC-1O+
- EXISTING EXTERIOR SCONCE — ESC-1 O+
- EXTERIOR GROUND UP LIGHT - E-9
- EXTERIOR SURFACE MOUNTED - E-8 — E-8
- EXTERIOR DIRECTIONAL - E-6 or E-10
- EXTERIOR DOWN LIGHT - E-5
- EXTERIOR TAPE LIGHT - E-2 — E-2
- EXTERIOR STEP LIGHT- E-1 — E-1
- PENDANT LIGHT - 50W — P-1
- COVE LIGHTS - CO-1 THROUGH C0-3 — CO-1
- LOW LEVEL W/ SENSOR - LL-1 — LL-1
- LINEAR CLOSET LIGHT- CL-1 OR CL-2 — CL-1
- ACCENT MIRROR LIGHT- ML-1 — ML-1
- ACCENT LIGHT- AC-5 — AC-5
- ACCENT LIGHT- AC-1 THROUGH AC-4 — AC-1
- PIN LIGHTS LIGHTS - PL-1 THROUGH PL-3 — PL-1
- DOWN LIGHTS - DL-1 THROUGH DL-16 — DL-1
- SPECIALTY PENDANT - 300W
- SURFACE WALL MOUNTED - 50W — SC-1
- SURFACE MOUNTED T8 - 2X28 W
- PENDANT MOUNTED T8- 2X28 W
- SURFACE MOUNTED- SF-1
- 2'X4' FLUORESCENT - DC-2 OR DC-4 — DC-2
- 2'X2' FLUORESCENT - DC-1 OR DC-3 — DC-1

REFLECTED CEILING PLAN FINISHES LEGEND

NOTE:
PROVIDE DIRECT-APPLIED PLASTER FINISH OVER DENSGLASS FOR CORRIDOR CEILINGS ONLY

- REFER TO SPECS DETAILS FOR ACCESS HATCH TYPES
- CERAMIC TILE CEILING
- EXPOSE STRUCTURE (ABOVE)
- EXTERIOR CEM. PLASTER - SMOOTH TROWEL FIN.
- CEILING HEIGHT ABOVE FINISH FLOOR — 9'-6" A.F.F.
- LAY-IN ACOUSTICAL TILE CEILING
- SUSPENDED GYPSUM BOARD CEILING (USE W.R. GYP. BD. AT WET AREAS)
- NO CEILING; OPEN TO STRUCTURE ABOVE — OTSA

REVISIONS			
BY	DATE	DESCRIPTION	
-	05/30/2013	Milestone 02	
-	06/04/2013	Milestone 03	
-	06/06/2013	Milestone 04	
-	06/27/2013	Milestone 05	

hla

howard laks architects

1545 twelfth street
santa monica, ca 90401
voice - 310-393-4455
fax - 310-393-2230

CONSULTANTS

710 WILSHIRE BOULEVARD

MIXED-USE HOTEL PROJECT
SANTA MONICA - CALIFORNIA 90401

FIFTH FLOOR RCP

DRAWN: AJH/SC
CHECKED: HLA
APPROVED: –
SCALE: 1/8" = 1'-0"
SHEET: A-511
DATE: June 25, 2013
PROJECT NUMBER: HLA 0000000–00000