



LIGHT FIXTURES LEGEND

NEW EXTERIOR SCONCE	EXSC-10H	EXTERIOR TAPE LIGHT - E-2	ML-1
EXISTING EXTERIOR SCONCE	ESC-1 CH	EXTERIOR STEP LIGHT - E-1	ES-1
RECESSED EXTERIOR PLASTER ACCESS PANEL		PENDANT LIGHT - 50W	P-1
RECESSED STAINLESS STEEL ACCESS PANEL		COVE LIGHTS - CO-1 THROUGH CO-3	CO-1
RECESSED DRYWALL ACCESS PANEL		LOW LEVEL W/ SENSOR - LL-1	LL-1
IN WALL HORN STROBE, GRAINGER #160826		LINEAR CLOSET LIGHT - CL-1 OR CL-2	CL-1
EXTERIOR FLOOD LIGHT			
EXTERIOR GROUND UP LIGHT - E-9	E-9		
EXTERIOR SURFACE MOUNTED - E-8	E-8		
EXTERIOR DIRECTIONAL - E-6 or E-10			
EXTERIOR DOWN LIGHT - E-5	E-5		

ACCENT MIRROR LIGHT - ML-1	ML-1	SURFACE WALL MOUNTED - 50W	SC-1
ACCENT LIGHT - AC-5	AC-5	SURFACE MOUNTED T8 - 2X28 W	
ACCENT LIGHT - AC-1 THROUGH AC-4	AC-1	PENDANT MOUNTED T8 - 2X28 W	
PIN LIGHTS LIGHTS - PL-1 THROUGH PL-3	PL-1	SURFACE MOUNTED - SF-1	
DOWN LIGHTS - DL-1 THROUGH DL-16	DL-1	2X4' FLUORESCENT - DC-2 OR DC-4	DC-2
SPECIALTY PENDANT - 300W		2X2' FLUORESCENT - DC-1 OR DC-3	DC-1

NOTE:
PROVIDE DIRECT-APPLIED PLASTER FINISH OVER
DENSGLASS FOR CORRIDOR CEILINGS ONLY

REFLECTED CEILING PLAN FINISHES LEGEND

REFER TO SPECS DETAILS FOR ACCESS HATCH TYPES		CEILING HEIGHT ABOVE FINISH FLOOR	3'-6" AFF.
CERAMIC TILE CEILING		LAY-IN ACOUSTICAL TILE CEILING	
EXPOSE STRUCTURE (ABOVE)		SUSPENDED GYPSUM BOARD CEILING (USE W.R. GYP. BD. AT WET AREAS)	
EXTERIOR CEM. PLASTER - SMOOTH TROWEL FIN.		NO CEILING; OPEN TO STRUCTURE ABOVE	OTSA