

<p>VISUAL CHARACTER NOTES:</p> <ul style="list-style-type: none">CHARACTERS AND THEIR BACKGROUND HAVE A NON-GLARE FINISH AND CONTRAST TO EACH OTHER, LIGHT-ON-DARK OR DARK-ON-LIGHT, WITH A HORIZONTAL FORMAT PER CBCIT IS PREFERABLE, ALTHOUGH NOT REQUIRED TO ALSO USE VISUAL CHARACTERS IF THE SIGN HAS BOTH RAISED CHARACTERS AND BRAILLE AND THE RAISED CHARACTERS CONTRAST TO THE BACKGROUND, LIGHT-ON-DARK OR DARK-ON-LIGHT, WITH A NON-GLARE FINISHIF VISUAL CHARACTERS ARE ALSO USED WITH RAISED CHARACTERS AND BRAILLE THEY CAN BE EITHER PART OF THE SAME SIGN OR A SEPARATE SIGN AND ARE REQUIRED TO COMPLY WITH FINISH AND CONTRAST, HORIZONTAL FORMAT, AND WITH STROKE THICKNESS PER CBCSIGNS REQUIRED TO HAVE VISUAL CHARACTER CAN BE IN UPPERCASE, LOWERCASE, OR A COMBINATION, BUT CAN NOT BE ITALICS, SCRIPT OR HIGHLY DECORATIVEWIDTH OF THE UPPER CASE LETTER 'O' IS BASED ON THE HEIGHT OF THE UPPERCASE LETTER 'Y' OF 50% MINIMUM TO 110% MAXIMUM PER CBCSTROKE THICKNESS IS 10% MIN TO 20% MAXIMUM OF THE HEIGHT OF THE UPPER-CASE LETTER 'Y' PER CBCCHARACTER SPACING WITHIN A WORD IS 10% TO 35% OF CHARACTER HEIGHTLINE SPACING BETWEEN BASELINES OF TEXT ROWS IS 135% TO 170% OF CHARACTER HEIGHTVISUAL CHARACTER MINIMUM HEIGHT IS BASED UPON AN UPPER CASE LETTER 'Y' AND IS DEPENDENT UPON HEIGHT AFF, WITH 40" MINIMUM AND HORIZONTAL VIEWING DISTANCE FROM THE SIGN TO AN OBSTRUCTION PREVENTING CLOSER APPROACH<ul style="list-style-type: none">TO ≤ 70" HEIGHT AFF<ul style="list-style-type: none">≥ 72" VIEWING DISTANCE = 8/3" HT CHARACTERS≥ 72" VIEWING DISTANCE = 5/8" HT + 1/8"/FT VIEWING DISTANCE OVER 72"> 70" TO ≤120" HEIGHT AFF<ul style="list-style-type: none">< 180" VIEWING DISTANCE = 2" HT CHARACTERS≥ 180" VIEWING DISTANCE = 2" HT + 1/8"/FT VIEWING DISTANCE OVER 180"> 120" HEIGHT AFF≥ 21" VIEWING DISTANCE = 3" HT CHARACTERS ≥ 21" VIEWING DISTANCE = 3" HT + 1/8" FT OF VIEWING DISTANCE OVER 21"		<p>LOCATE SYMBOL IN JAMB 44" A.F.F.</p>				<p>SCOTCHLITE NON-REFLECTIVE FILM BACKGROUND COLOR: GREEN 3M 580-76 OR APPROVED EQUAL</p> <p>COPY: WHITE 3M 550-10</p> <p>EDGES & CORNERS: 1/2" RADIUS</p> <p>CODE SECTION CBC 1129B.5 MIN. 17 X 22 W/ LETTERS SIZE MIN. 1"</p>				<p>BACK PLATE</p> <p>1/4" PHOTO POLYMER EASE EDGES & CORNERS COLOR: -----</p> <p>TEXT AND IMAGES (RAISED 1/32")</p> <p>TEXT: 1" OPTIMA BOLD NUMERAL 5" OPTIMA BOLD COLOR: -----</p> <p>BRILLE TEXT (SHOWN)</p> <p>RAISED 1/40" AND MATCHING GRAPHIC TEXT AND NUMERALS</p> <p>SECURE TO WALL WITH DOUBLE-FACE TAPE AND SILICONE</p>		<p>BACK PLATE</p> <p>1/4" PHOTO POLYMER EASE EDGES & CORNERS COLOR: •</p> <p>NON-REFLECTIVE SYMBOL TO CONTRAST TO DOOR EITHER DARK-ON-LIGHT OR LIGHT-ON DARK; IF NOT ALL RESTROOMS ARE ACCESSIBLE THE ACCESSIBLE RESTROOM ARE REQUIRED TO HAVE AN ISA-PLACE ON DOOR SYMBOL AND THE NON-ACCESSIBLE RESTROOMS HAVE A DIRECTION SIGN WITH AN ISA.</p> <p>SECURE TO DOOR WITH DOUBLE-FACE TAPE AND SILICONE</p> <p>NOTE: AT STAFF TOILET PROVIDE 1" HIGH OPTIMA BOLD TEXT INDICATING "STAFF"</p> <p>COLOR TO BE SELECTED BY ARCHITECT. MOUNT 58" TO 60" A.F.F. TO THE CENTER LEFT TO RIGHT WITHIN 1" OF THE DOOR CENTERLINE</p>											
<p>EMERGENCY MEDICAL</p>		30		<p>POOL RULES 7TH FLOOR</p>		25		<p>FUEL EFFICIENCY PREFERRED PARKING</p>		20		<p>INTERNATIONAL SYMBOL OF ACCESS</p>		15		<p>STAIR WELL IDENTIFICATION (FIRE)</p>		10		<p>WOMEN'S TOILET ROOM DOOR SYMBOL</p>		5	
<p>STANDARD STALL W/ COLUMN ON SINGLE SIDE</p>		29		<p>EMERGENCY & CPR 7TH FLOOR</p>		24		<p>TITLE 1</p>		19		<p>ACCESSIBLE PARKING CODE SIGN</p>		14		<p>STAIR WELL IDENTIFICATION</p>		9		<p>MENS TOILET ROOM DOOR SYMBOL</p>		4	
<p>BRaille</p> <ul style="list-style-type: none">UPPER CASE LETTERS ARE RESERVED FOR TYPICAL CAPITALIZATION SUCH AS NAMES AND ACRONYMSBRAILLE TO BE CONTRACTED (GRADE 2) WITH SPACING OF DOTS IN AND WITHIN ADJACENT CELLS PER CA BRAILLE STANDARDS PER CBCBRAILLE DOTS HAVE A ROUNDED OR DOMED SHAPE WITH A BASE DIAMETER OF .059" - .063"BRAILLE DOTS ARE .1" ON CENTER WITHIN CELLS, .3" BETWEEN CORRESPONDING DOTS IN ADJACENT CELLS, .395" TO .4" BETWEEN CORRESPONDING DOTS IN THE CELL BELOW, AND RAISED .025" MINIMUM TO .037" MAXIMUM FROM THE BACKGROUNDBRAILLE IS POSITIONED 1" MINIMUM BELOW THE RAISED CHARACTERS AND ANY RAISED BORDERS OR ELEMENTS, AND 1" MAXIMUM SPACE FROM RAISED CHARACTERS TO BRAILLE PER CBCWHERE RAISED CHARACTERS ARE MULTI-LINED, BRAILLE IS PLACED BELOW ALL LINES OF RAISED CHARACTERSBRAILLE TO BE FLUSH LEFT OR CENTERED ON RAISED CHARACTERS IN A HORIZONTAL FORMAT PER CBC																							
<p>GENERAL NOTES</p>		33		<p>STANDARD STALL</p>		28		<p>SPA WARNING 7TH FLOOR</p>		23		<p>ELEVATOR LOCATOR</p>		18		<p>ACCESSIBLE PARKING FOR VANS</p>		13		<p>OCCUPANCY</p>		8	

CONSULTANTS		REVISIONS	
DATE	BY	DATE	BY
6/27/2015	Michael G2	6/27/2015	Michael G2
09/14/2015	Michael G3	09/14/2015	Michael G3
10/29/2015	Michael G4	10/29/2015	Michael G4
6/27/2016	Michael G5	6/27/2016	Michael G5



howard laks architects

voice : 310-393-4465
fax : 310-393-2230

1545 twelfth street
santa monica, ca 90401

CONSULTANTS

710 WILSHIRE BOULEVARD

MIXED-USE HOTEL PROJECT

SANTA MONICA - CALIFORNIA, 90401

SIGNAGE

DRAWN	SKH
CHECKED	H.L.A.
APPROVED	-
SCALE	AS NOTED
SHEET	
A-701	
DATE	June 25, 2013
PROJECT NUMBER	H.L.A. 00000000-00000