GENERAL NOTES:


ALL JUNCTION BOXES AND THE CONDUITS CONNECTING THEM SHALL BE LOCATED MORE THAN 5' FROM THE PERIMETER OF THE POOL. PANEL "P" IS LOCATED IN POOL EQUIPMENT ROOM BELOW.

SHEET NOTES:

- CONNECT POOL LIGHTS TO CIRCUIT SHOWN VIA LIGHTING CONTROLLER, AS REQUIRED. VERIFY MANUFACTURERS REQUIREMENTS. WHERE THERE ARE MULTIPLE HOME RUNS TO THE SAME BREAKER, SPLICE AS NECESSARY AND AS ALLOWED BY CODE.
- PENTAIR INTELLIBRITE 5G LOW VOLTAGE LED POOL LIGHTS. VERIFY MANUFACTURERS REQUIREMENTS.
- MOUNT JUNCTION BOXES (HYDREL #1719) IN PLANTER WALLS OR PEDESTALS AND PROVIDE BLANK FACE GFCI FOR PROTECTION OF LIGHTS AND RECEPTACLE AT EACH LOCATION. VERIFY EXACT LOCATIONS WITH ARCHITECT.
- THERE SHALL BE A MAXIMUM OF THREE 90 DEGREE BENDS IN THE CONDUIT BETWEEN THE LIGHT NICHE AND THE PULL BOX.
- 15 MINUTE TIMER SWITCH & EMERGENCY SHUT OFF SWITCH.
 VERIFY EXACT LOCATION WITH ARCHITECT.

Plan Check Submittal
Plan Check Re-Submittal Delta 01 A
Plan Check Re-Submittal 02 Delta 02 A
Plan Check Re-Submittal 02 Delta 03 A

CONSULTANTS



AS NOTED

OCTOBER 17, 2014